





MOD.

CLIENTE UTILIZZATORE / CUSTOMER USER

S6 - CXTT 1350

COMMESSA DI PRODUZIONE

ANDREWEX SP. Z 0.0.

QS1412MM013

VOLUME ARIA ASPIRAZIONE / DUST EXTRACTION REQUIREMENT			m <sup>3</sup> /h		
BOCCHE OUTLETS	N° DIAMETRO BOCCA OUTLET DIAMETER	mm.	20 m/s	24 m/s	28 m/s
6		100		4068	4746
2		120		1954	2280
6		160		10422	12156
1		180		2198	2565
.		.		.	.
.		.		.	.
.		.		.	.
.		.		.	.
<b>TOTALE VOLUME / TOTAL REQUIR.</b>			m <sup>3</sup> /h	<b>18642</b>	<b>21747</b>
<b>MAX VOLUME ARIA RICICLATA</b>			m <sup>3</sup> /h	.	.
<b>VENT. DEPRESSIONE / VACUUM FAN</b>			m <sup>3</sup> /h	1600	

<b>CONSUMO ARIA COMPRESSA / COMPRESSED AIR REQUIREMENT</b>			<b>NI/min</b>		
GRUPPI / UNITS	QUANTITA' QUANTITY	N°	6 BAR		
CONTROLLO NASTRI / BELTS CONTROL	3		300	300	
<b>SOFFIATORI / BLOWERS</b>	QUANTITA' QUANTITY	N°	4 BAR	5 BAR	6 BAR
SOFFIATORI PULIZIA NASTRI LONGITUDINALI AIRJET BLOWERS FOR LONGITUDINAL BELTS	4		2184	2652	3120
SOFFIATORI PULIZIA NASTRI TRASVERSALI AIRJET BLOWERS FOR CROSS BELTS	1	.	294	357	420
SOFFIATORI PULIZIA PANNELLI AIRJET BLOWERS FOR PANELS CLEANING	1		672	816	960
SOFFIATORI PULIZIA TAPPETO AIRJET BLOWERS FOR FEEDBELT	1		364	442	520
<b>TOTALE CONSUMO ARIA / TOTAL AIR REQUIR.</b>		<b>NI/min</b>	<b>3814</b>	<b>4567</b>	<b>5320</b>

<b>TOTALE POTENZA / TOTAL POWER (V.</b>		<b>400 ) KW</b>	<b>75</b>	<b>(50 Hz)</b>	<b>(60 Hz)</b>
<b>NASTRI ABRASIVI / SANDING BELT</b>			<b>1380</b>	<b>X</b>	<b>2620</b>
Dimensioni = Larghezza x sviluppo Dimensions = Width x Length (mm)	Longitudinale Longitudinal		150	<b>X</b>	5450
	Trasversale Cross				

- 1 cubic meter = 35,315 cubic feet (cubic feet = cubic meter x 0,02832)
- 1 bar = 14,223 pound for square inch (pound for square inch = bar x 0,0703)
- 1 KW = 1,36 CV (KW = CV x 0,7354)
- 1000 NI/min = 1 m<sup>3</sup>/min = 35,315 CFM

Ci riserviamo il diritto di apportare modifiche / We reserve the right to bring modifications at any time without notice