





MC190S-I SERIES

# **Main Improvements:**

## Availability for wide application

MCWEL model is line up to suit a wide range of applications such aspneumatic tools drilling and blasting.

AIR PRESSURE: 7 bar

FAD: 190 CFM / 5.4 m³/min

## **Easy Starting in Cold Weather**

This compressor is superior in cold weather starting.

## **Meters with Luminous Lights**

Meters on operation panel are equipped with luminous light.

#### **Reliable Warning Signal**

Warning signals have luminescent diode and so become more reliable.


### **Double Element Air Cleaner**


Double element air cleaner prevents dust from entering when replacing element.

#### **Easy Cleaning of Cooling System**

This compressor is so designed that the interiors of radiator and oil cooler and also fuel tank can be easily and quickly cleaned







## **COMPRESSOR**

Rotary twin screw, single stage, Type

oil-cooled

Free air delivery 5.4 m<sub>3</sub>/min(190 cfm)

Working pressure 7 bar (100 psi)

Suction port closing in connection Unloader

with stepless speed regulator

Forced lubrication by Lubrication system

compression pressure

Direct coupling with rubber Driving system

Oil cooling Air-cooled

Air cleaner Dry paper filter type

## OIL SEPARATOR-RECEIVER TANK

Type Vertical,cylindrical,full-welded

Shell dia 250 mm Shell length 784 mm Capacity 32 L Max.working pressure 1.58MPa Hydraulic test pressure 2.37MPa Air outlet valve 3pcs x 3 /4"

#46 Recommend Oil type

**INSTRUMENTS & GAUGES** 

Oil pressure switch

Air Pressure gauge

Fuel level gauge

Stop button

Starter switch

Starting Loader

**GAUGES** 

**EMERGENCY STOP DEVICES** 

Engine coolant temperature switch

Compressor oil temperature switch

Discharge air temperature switch

Engine speed down switch

## **DIESEL ENGINE**

ISUZU 4JB1ZY-01 Model

Water-cooled,4-cycle, Type

Direct-Injection,

Turbocharged No. Of cylinders

Bore x stroke

93 mm x 102 mm Total displacement

2.771 liters Compression ratio Rated output 18.2:1

50 kW, 2,500rpm Max.torque

172 N.m/approx.2,000rpm Governor

Mechanical Alternator Starting motor DC 12 V, 35 A DC 12 V, 2.2 kw Battery

80AH X 1 pcs, 580CCA Air cleaner

Two-stage dry type

# **DIMENSIONS & WEIGHT**

LxWxH2100 x 980 x 1100 mm

Tachometer

Hour meter

Engine oil pressure

Engine coolant temp

Discharge air pressure

Discharge air temp

Weight 930 Kg

# LIQUID CAPACITY

Fuel tank capacity 80 liters Engine oil capacity 5 liters Coolant capacity 8 liters Compressor oil capacity 32 liters

## JPN INDUSTRIAL TRADING PTE LTD

13A Pandan Crescent Singapore 128478

13A Paliuan C... TEL: +65 6288 9991 Email: sales@jpn.sg http: www.jpn.sg







- Operate safely in accordance with proper operation manual.
- To prevent trouble and accidents, perform daily and preventive maintenance checks without fail.