

Freza CNC 5 axe MAZAK VARIAXIS i600 SmoothX 1583 ore

Diametru max. piesa	700 mm
Inaltime max. piesa	450 mm
Deplasare axa X	510mm
Deplasare axa Y	910mm
Deplasare axa Z	510mm
A -axa pivotanta	-120°+30°
B -axa pivotanta	nu
C -axa pivotanta	+/-360°
Capacitate incarcare masa	500 kg
Axe	
Motoraxe marime/turatie	SK-40/12.000 1/min
Putere motor principal	100% /15kW
Moment torsiune	200Nm
Viteze de deplasare	
Axa X/Y/Z	60/60/56 m/min
Axa pivotanta A/C	18000°/min
Aschiere axa X/Y/Z	56 m/min
Magazin de scule si schimbator de scule	
Numar de scule	40
Diamatru max de scule	90 mm
Diamatru max fara scula vecina	130 mm
Capacitatea tancuri/rezervoare	
Tanc ulei lubreficant	1,80 L
Tanc agent de racire	600 L
Tanc ulei de racire axa	56 L
Precizie	
Axe X/Z	0,012/0,012mm
Axe Y	0,016mm
Axe A	14s
Repetabilitate X/Z	0,007mm
Repetabilitate Y	0,009mm
Repetabilitate A	8s
Repetabilitate B	nu
Repetabilitate C	8s
Marime utilaj	
Lungime	3980 mm
Latime	2200 mm
Inaltime max.	3187 mm
Greutate max.	13.000 kg
Caracteristici instalare curent	
Putere instalata	52,90 kVA
Frecventa curent	50/60 Hz+/-1Hz
Caracteristici instalare aer	
Presiune	0,5-0,9 Mpa
Necesar-max	360 L/min