

hyCLEANER®



hyCLEANER® **red** EVO I

- The **hyCLEANER® red EVO I** cleans different forms of façades, surfaces and materials: very gentle, effective, fast and above all, economic. The machine works with high-pressure water and does not need any electrical connection. Both, the glass and the frames are cleaned simultaneously. All water leading elements are made out of stainless steel. Purified-water can be used and the glass surfaces dry up, leaving no streaks behind.
- A further advantage of **hyCLEANER® red EVO I** is the running wheels. They do not leave any marks on the surface of the façade - gentle cleaning can be so easy!

Technical data

Machine

Brush width	approx. 1550 mm
Brush diameter	approx. 550 mm
Balance of movement	max. 1000 mm
Running wheel Ø big	500 mm
Running wheel Ø small	260 mm
Total weight	min. 120 kg
	min. 20 kp/m ² (197 N/m ²)
Traffic load	max. 82 kp/m ² (807 N/m ²)

Motor

Water pressure	min. 120 bar (1740 psi) max. 160 bar (2300 psi)
Water quantity	min. 9 l/min. (1.98 gal/min (UK)) max. 12 l/min. (2.64 gal/min (UK))
Revolutions regulated via water quantity	yes
Lowering speed	max. 24 m/min.
Performance*	max. 18 m ² /min.
*depending on degree of soiling	

Alterations in construction reserved / 05.08.2015

TG hyLIFT®

TG hyLIFT® GmbH
Maybachstraße 6
D-48599 Gronau
phone +49 2562 99254 0
fax +49 2562 99254 10
info@tg-hylift.com
www.tg-hylift.com
www.hyCLEANER.eu