

QUOTATION VEMAG SAUSAGE LINE



The line include:

HP10 E type 161



- Continuous vacuum filler for straight filling and portioning

Machine features:

All in one 250 l hopper with counter arm and reinforced scraper, tipping aid and hopper lock

- Integrated vacuum pump with a suction capacity of 16 cbm/h
- Standard double screw
- Standard double screw housing

- Filling horn holder
- Integrated can-bus control:
Graphical display of all settings, functions and fault information on tft Colour screen
- Program memory for 99 filling programs,
Portioning weights can be set from 1 to 99,999 grammes,
Portioning speed > 950 portions/minute, depending on weight

- VEMAG DuoDrive with separate drive for double screw and feed:
double screw drive with 7.0 kW AC servo
- Infeed scroll drive with 4 kW AC motor with frequency inverter
- Infinitely controllable filling rate up to 5,700 kg/h (based on a double screw with a 48 mm pitch)
- Socket for external supplementary equipment
- Whole machine frame in stainless steel with fold-out step
- Nominal output, total: 14 KW ;21 A

VEMAG lifting and tipping device for HPE with 250 l hopper

- To fit standard trolley, 200 l capacity

VEMAG high-performance linking machine for identical lengths with casing magazine LPG 209:



- For linking and portioning all common types of casing in identical lengths using mechanical dividers on the following basis:
- Divider belt with a fixed portion length changeable by using quick-release
- One twin head for rapid casing changes
- With automatic casing end detection with shutoff
- ONLY for CAN BUS fillers
- With casing magazine for collagen, polyamide or cellulose casings
- With magazine and casing pusher
- Fully automatic loading for collagen, polyamide or cellulose casings and semi- automatic application for natural casings
- Linking and transfer to hanging or separating
- For sausage calibres from 13 to 40 mm
- For shirred casing lengths up to 430 mm
- For sausage lengths from 20 mm to approx. 400 mm
- Portioning speed: 1300 port. /min natural casings, 2200 port. /min artificial and collagen casings
- Automatic synchronization of belt, filling- and linking speed
- Control of the frequency-controlled drives and all functions by the VEMAG portioning computer
- Incl. one set of divider belts and a linker horn set with casing brake
- Nominal output, total: 6,0 KW

- Compressed air: 6 bar, 10 l/min

VEMAG sausage hanging machine AH type 212



VEMAG Flexible sausage hanging machine AH type 212, long version

- Basic unit WITHOUT connection
- Only in connection with VEMAG vacuum filler with CAN-BUS control
- For automatically hanging sausages in natural, collagen and artificial casings
- From 25 mm infinitely adjustable pitches between the hooks to suit calibre
- Hooks can be arranged in easily selected groups for equal quantity of sausages per stick. - Adjustment options by means of the portioning computer.
- Gap function: either filled or empty portion
- Two operating heights for easy customizing and simple removal of the sausage string
- AC servo drive controlled by the VEMAG portioning computer of the vacuum filler ONLY with CAN-BUS
- Ramp control for vibration-free hook feed
- Adjustment options on the portioning computer for:
 - Number of sausages per hook (1 up to 30) depending on type of sausage (e.g. cocktail sausages = high number of sausages per hook, max. 1500 g)
 - Maximum hook feed 200/min
 - Total nominal output: 0,5 KW
 - Total length 4150 mm

Total VEMAG sausage line dimensions:

Length – 8000 mm

Width – 1350 mm