

Position Nr.: 2065

Edgepolisher COMANDULLI, Type: MUSA 7 + 4 DX , Year of Production: 2016

Machine No.	00216
Working direction	From right to left
Feed speed	0-3 m/min
Conveyor belt width	600 mm
Working thickness	10 – 80 mm
Min. workpiece width	80 mm
Max. workpiece width (without side support)	1200 mm
Max. workpiece width (with side support)	3000 mm
Working height	750 mm
Working Units	
1 calibrating spindle	Vertical and horizontal positioning for 260 mm diameter flat diamond Wheel
7 Edge polishing spindles	with oscillating floating system
4 beveling spindles	2 x 45 °(upper/ lower) for bevel generation, equipped with the TMM3 mechanical locking system
	2 x 45° (upper/lower) for polishing the previously generated bevels
Equipment	
Colour touchscreen control	
Automatic water valves	
Roller tables	2 x 1,5 m
Power supply	3 x 415 V +PE/ 50 Hz
Rated current	52 A
Installed power	22 kW
Suitable for	Natural stone, quartz composite, ceramic materials
Dimensions (excluding roller tables)	L=5150 mm x W=1800 mm x H=1740 mm
weight	4000 kg

(Subject to errors, technical modifications and prior sale)