

Baler Presto, type HPK 50 HS, 50 t pressing force, yoc 2014, approx. 9,000 operating hours, drive power 30 kW, with conveyor and wire stations



The machine was overhauled by the manufacturer Presto in 2022 for €21,422 net, is in good condition and can be used immediately.

Technical data baler:

Manufacturer Presto GmbH & Co. KD, Bad Laer, Germany

Typ HPK 50 HS

Year of construction 2014

Hours of operation approx. 9,000 hours

Press power 50 tons

Specific press capacity 752 kN/m²

Feed channel 1,600 x 650 mm (l x w)

Capacity per cycle time 1,06 m³

Theoretic cycle time 19 sec.

Bale size 700 x 950 mm (w x h)

Driving motor 30 kW

Rated current 56 A

Tying system 4-fold horizontal, fully automated

Throughput rate at a

bulk weight of 35 kg/cbm approx. 5,5 tons/hour

bulk weight of 50 kg/cbm approx. 8,8 tons/hour

bulk weight of 100 kg/cbm approx. 12,7 tons/hour

Bale weight approx. 450 kg, depending on material

SPS controller Siemens S7 1200

Operating panel Siemens SIMATIC Touch

Space required 9,920 x 2,920 mm (l x w)

Transport dimensions only baler 8,420 x 1,770 x 2,400 mm (l x w x h)

Machine weight baler approx. 10,500 kg

Scope of delivery:

1 conveyor belt

Baler Presto, type HPK 50 HS, 50 t pressing force, yoc 2014, approx. 9,000 operating hours, drive power 30 kW, with conveyor and wire stations

1 baler with large feed chute
4 wire reel boxes for 40 kg wire reels on board
4 wire stations for 500 kg wire reels, without wire
1 item of machine documentation

Comments:

The machine was overhauled by the manufacturer Presto in 2022 for €21,422 net, is in good condition and can be used immediately. The documentation (Manual, CE, electr./hydr.-drawings), are completely available. Inspections are possible after agreement. We will not assume liability for the given technical data and possible errors.

Baler Presto, type HPK 50 HS, 50 t pressing force, yoc 2014, approx. 9,000 operating hours, drive power 30 kW, with conveyor and wire stations



Baler Presto, type HPK 50 HS, 50 t pressing force, yoc 2014, approx. 9,000 operating hours, drive power 30 kW, with conveyor and wire stations

