



Chassis serial number: 5765886

Chassis type: S 530 A6x2/4NB

General information			
VIN-code	YS2S6X20005765886	Factory warranty, valid until	2026-04-19
Factory warranty is only valid if all paragraphs in Scania's Global Warranty Manual is fulfilled		Start-up date	2025-04-19
Invoice date	2024-12-23	Assembly date	2024-11-19
Crankshaft assembly date	2024-11-08	Current distributor, country	BE
Current distributor, number	61011	Ordering distributor, country	BE
Ordering distributor, number	61011	Local dealer, number	-
Gross laden train weight	20	Order Number	1713852
Order type	A	Delivery mode	CBU
Status	To enduser	Scrap date	-
POP-ID	28-1389		

00 General			
Assembly level	Completely Build Up	Development level	6
Product class	Truck	Wheel configuration certified	6x2/4
Front wheel drive	no	Axle distance	4100 mm
Steering wheel position	left hand	Chassis width	2550 mm
Chassis adaptation	articulated	Chassis height	normal
Driver´s manual language	dutch	Driver´s manual extra language	without
Plate language	english	Axle weight front technical	9000 kg
Bogie weight, technical	19000 kg (7500 + 11500)	Technical max axle weight 1st	9000 kg
Technical weight on 2nd axle	7500 kg	Technical weight on 3rd axle	11500 kg
Technical weight on 4th axle	not valid	Technical weight on fifth axle	not valid
GVW legal	26000 kg	GVW additional weight low emission vehicle	without
Legal weight 1st axle	9000 kg	Legal weight 2nd axle	7500 kg
Legal weight 3rd axle	11500 kg	Legal weight 4th axle	without
Legal weight 5th axle	without	Legal weight 6th axle	without
GTW technical	64000 kg	GTW technical part 2	0 kg
GTW technical part 3	0 kg	GVW legal part 2	0 kg
GVW technical	28000 kg	GTW Legal	85000 kg
Preparation for toll collect	without		

01 Engine			
Propulsion	combustion engine	Engine power kW	390
Power code	530hp	Engine type, vehicle	DC16 120/530 hp
Engine type symbol	Transfer code	Engine type symbol	DC16 120 L01
Engine serial number	1218177	Cylinder block generation	3
Engine speed limit low oil pressure	without	EGR system	without
EGR cooling	not valid	Emission level	Euro 6
Engine stroke volume	16 litres	Engine management system	EMS10
Automatic engine shutdown	without	NOx control	with
Torque reduction NOx-control	with	Power Take-Off ED	without
PTO ED electrical preparation	without	Turbocharger duty class	special
Air intake	front	Air cleaner engine fire-resistant	without
Air cleaner supplier	Mann	Noise suppression	79/81 dBA R51.03
Noise level additional requirement/regulation	without	Noise encapsulation engine	without
Noise encapsulation engine side	with	Noise encapsulation engine behind	without
Crankcase gas cleaning type	centrifugal	Crankcase ventilation type	open
Oil level sensor engine	with temperature sensor	Oil level sensor monitoring	with
Oil dipstick oil volume adaptation	normal	Oil sump material	plastic
Oil quality engine	Scania LDF-4	Powertrain oil type	normal
Air intake throttle engine	with		

02 Cooling System			
Radiator area	100 dm2	Fan control	electronic
Charge air cooler curtain	without	Fan, driving	crankshaft assy
Fan, diameter	813 mm	Fan blade quantity	11
Fan, gear ratio	1:1	Coolant pump flow	470 dm3/min
Coolant pump controlled flow	without	Temperature regulator	80 degrees

03 Fuel And Exhaust Systems			
Fuel	diesel	Fuel alternative diesel adaptation	without
Injection system	common rail	Fuel tank	LH side
Fuel volume, right side	without	Fuel volume, left side	420 dm3
Fuel theft alarm	without	Fuel tank sectional area left-hand side	large
Fuel tank sectional area right-hand side	without	Fuel tank material	aluminium



Chassis serial number: 5765886

Chassis type: S 530 A6x2/4NB

Selective Catalytic Reduction	with	SCR reductant tank volume outside frame right-hand side	without
SCR reductant tank volume outside frame left-hand side	without	SCR reductant tank volume under frame left-hand side	76 dm3
SCR heating system	with	SCR heating system type	coolant
SCR catalytic converter volume	26,9 dm3	SCR catalytic converter coating type	DW3811
Fuel heater	with	Fuel tank location	normal
Fuel filter chassis mounted	without	Fuel splash protection	with
Exhaust outlet, direction	right hand	Silencer serial number	24313024
Silencer length	900 mm	Exh silencer heat cov painted	without
DPF particulate filter	with	First DPF serial number	243120480005
Second DPF serial number	243120430000	Particulate filter sensor	with
DPF exhaust flow type	full filter	DPF particulate filter volume	23,4 dm3
DPF particulate filter coating	TEX-1747		

04 Clutch			
Clutch, frictiontype	K432 26	Clutch wear protection	without
Clutch system	automatic		

05 Gearbox			
Gearbox	G33CM1	Gearbox serial number	2100715
Gearbox oil temperature warning level	without	Gearbox management system	TMS
Transmission management system	TMS3	Engine power kW	390
Opticruise	with	Starter interlock gearselector	with
Acceleration control	without	Performance modes	economy, standard, off-road
Manual gear change limitation	without	Cruise control with active prediction	with
Eco-roll	with	Road data registration	storage and use
Kickdown	with	Kick down signal	with
Gear shift control electronic	Opticruise	Gearbox type	AMT
Automatic neutral gear	without	Gear selector position	steering wheel
Transmission sensor constant	10	Oil cooling for gearbox	with
Refrigerant oil cooler gearbox	Refrigerant air	Retarder	without
Retarder system	without	PTO EG right-hand side	without
PTO EG left-hand side	without	PTO EG rear	without
PTO EG electrical preparation	without	PTO EG control total quantity	without
PTO EG top	without	Power take-off for clutch connection	without
Power take-off gear independent	without	PTO split shaft el. prep.	without
Noise encapsulation gearbox	without		

06 Propeller Shaft			
Propeller shaft type	P502	Propeller shaft length to rear axle	660 mm
Propeller shaft intermediate quantity	1	Intermediate propeller shaft 1 type to rear central gear	P512
Intermediate propeller shaft 1 length to rear central gear	850 mm		

07 Front Axle	
Front axle, type	AM640S

08 Rear Axle			
Rear axle, type	AD400SA	Load limit	at 11500 kg
Load distribution type	pressure ratio	Load transfer speed limitation	30 km/h
Load transfer manoeuvring	max load transfer request	Load transfer	with
Load transfer according to EC 97/27	yes	Oil filter rear axle	with
Oil quality driving axle	Scania STO 2:0 A FS	Axle gear type, rear axle	R780
Rear axle serial number	3304701	Rear axle gear ratio	2,71
Differential lock	with	Hub reduction, rear	without
Tag axle in front of rear axle	AM622S	Tag axle in front of driven rear axle	axle with steering
Tag axle behind driven rear axle	without		

09 Hubs And Wheels			
Rim material	steel	Rim type front axle	22.5X11.75 steel tubeless
Rim type rear axle	22.5x9.00 steel	Rim type tag axle in front of driven rear axle	22.5x9.00 steel
Rim type spare wheel	without	Rim diameter front axle	22.5
Rim diameter rear axle	22.5	Rim diameter tag axle in front driven axle	22.5
Rim diameter spare wheel	without	Rim width front axle	11.75



Chassis serial number: 5765886

Chassis type: S 530 A6x2/4NB

Rim width rear axle	9.00	Rim width tag axle in front of driven axle	9.00
Rim width spare wheel	without	Tyre dimension front axle	385/65 R22.5
Tyre dimension rear axle	315/80 R22.5	Tyre dimension tag axle in front of driven axle	315/80 R22.5
Tyre dimension spare wheel	without	Tyre pattern type front axle	Steer
Tyre pattern type rear axle	Drive	Tyre pattern type tag axle in front of driven rear axle	Drive
Tyre category front axle	Construction	Tyre category rear axle	Regional
Tyre category tag axle in front of driven rear axle	Regional	Tyre calculated rolling radius front	group C= 525 mm
Tyre calculated rolling radius drive	group C= 525 mm	Tyre rolling circumference driven rear axle	3298 mm
Front axle tyre rolling circumference	3248 mm	Drive tyre rolling circumference	3282 mm
Tag axle front tyre rolling circumference	3282 mm	Tyre supplier front axle	Flexible
Tyre supplier rear axle	Flexible	Tyre supplier tag axle in front	Flexible
Tyre speed index front axle	K=max. 110 km/h	Tyre additional speed index front axle	E=max. 120 km/h
Tyre load index front axle	164	Tyre additional load index front axle	158
Tyre load index rear axle	150	Tyre load index tag axle in front of driven axle	156
Tyre pressure monitoring	with		

10 Brakes			
White smoke limiter	without	Wheel brake	disc
Brake control	electronic	Hill hold	auto hold
Brake category	AB	Brake caliper supplier	Knorr
Brake chamber type 1st front axle	membrane + spring	Service brake chamber area first front axle	30"
Parking brake chamber area first front axle	14"	Brake chamber type 2nd front axle	not valid
Brake chamber type 1st rear axle	membrane+spring	Service brake chamber area first driven rear axle	24"
Parking brake chamber area first driven rear axle	30"	Brake chamber type 2nd rear axle	not valid
Brake chamber type trailing tag axle	not valid	Brake chamber type steered tag axle	membrane
Service brake chamber area tag axle front of driven rear axle	24"	Brake lining status display	percent
Anti vibration set in brake chamber	without	ABS/EBS system	6S/5M
Brake management system	EBS9	Advanced emergency braking	vehicle
Emergency braking indication	With	Air Processing System	air management
Compressor manufacture	Knorr 720 CR	Compressor clutch	with
Secondary brake	with double check valve	Trailer brake connection	without
Parking brake system	electropneumatic	Disengaging parking brake front	without
Trailer connector bracket	behind cab	Trailer brake coupling	with
Trailer hand control valve	without	Exhaust brake	with
Air tank volume, front	59 dm3	Air tank volume, rear	60 dm3
Air tank volume, extra	Without	Air tanks, rubber spacer	without
Compressed air tank position A1 volume	without	Compressed air tank position A2 volume	without
Compressed air tank position A3 volume	without	Compressed air tank position A4 volume	without
Compressed air tank position B1 volume	without	Compressed air tank position B2 volume	without
Compressed air tank position B3 volume	without	Compressed air tank position B4 volume	without
Compressed air tank position D1 upper volume	without	Compressed air tank position D2 upper volume	without
Compressed air tank position D3 upper volume	without	Compressed air tank position D4 upper volume	without
Compressed air tank position D5 upper volume	without	Compressed air tank position D6 lower volume	without
Compressed air tank position E1 volume	without	Compressed air tank position E2 volume	without
Compressed air tank position E3 volume	without	Compressed air tank position E4 volume	without
Compressed air tank position E5 volume	without	Compressed air tank position E6 volume	without
Compressed air tank position F volume	30 dm3	Compressed air tank position G1 volume	without
Compressed air tank position G2 volume	without	Compressed air tank position H1 volume	without
Compressed air tank position H2 volume	without	Compressed air tank position J1F volume	without
Compressed air tank J2F volume	without	Compressed air tank position J1 rear volume	without
Compressed air tank volume J2 rear	without	Compressed air tank K1 volume	without
Compressed air tank K2 volume	Without	Compressed air tank position L volume	without
Compressed air tank position M1 volume	15 dm3	Compressed air tank position M2 volume	15 dm3
Compressed air tank position N1 volume	without	Compressed air tank position N2 volume	without
Compressed air tank position N3 volume	without	Compressed air tank position Q2 volume	without
Compressed air tank position R volume	without	Compressed air tank position S1 volume	without
Compressed air tank position S2 volume	30 dm3	Compressed air tank position S3 volume	without
Compressed air tank position S4 volume	without	Compressed air tank position S1 temp volume	without
Compressed air tank position S2 temp volume	without	Compressed air tank position T volume	without
Compressed air tank position U1 upper volume	without	Compressed air tank position U2 lower volume	without
Compressed air tank position V1 volume	without	Compressed air tank position V2 volume	without
Compressed air tank position W volume	30 dm3	Compressed air tank position X1 volume	without
Compressed air tank position X2 volume	without	Compressed air tank position Y volume	without

11 Frame



Chassis serial number: 5765886

Chassis type: S 530 A6x2/4NB

Frame, type	F950	Frame reinforcement	without
Frame bend quantity	1	Chassis colour	Grey
Chassis colour grey	Sub Grey	Chassis front end width	1260 mm
Frame reinforcement crossmember rear suspension	without	Frame side member rear end	S
Bumper protrusion	0 mm	FUP directive	FUP device
Bumper beam vertical position	low	Underrun beam according to AR regulation	without
Chassis side cover	without		

12 Suspension			
Suspension type designation	B	Suspension system front	air
Shock absorber first front axle heavy duty	without	Suspension system rear	air
Air suspension rear type	2-spring	Air spring height, front	low
Level adjustment speed	fast	Level adj extra air tank	without
Level adjustment control truck/trailer	truck	Automatic lowering front	without
Alternative predefined chassis levels	1 extra drive + 2 memory	Trailer tag axle lift manoeuvring	with
Axle load display	front and rear	Level adjustment remote control body builder	without
Tag axle lift	with	Bogie designation, type	not valid
Bogie distance between first and second rear axle	1300 mm	Anti-roll bar, front	extra stiffness
Anti-roll bar stiffness first front axle	extra	Anti-roll bar tag axle	without

13 Steering			
Steering gear execution	BOSCH 8099	Steering gear serial number	004079
Front axle steering system type	hydraulic	Steering gear ratio	17-20:1
Steering system backup	hydraulic	Hydraulic pump flow	16 litre/minute
Hydraulic pump pressure	185 bar	Steering force 70/311/EEC	yes
Airbag steering wheel	without	Airbag side curtain	without
Steering wheel type	exclusive wood	Adjustable steering wheel	tilt+ slide
Steering angle 1st, RH turn	47 max	Steering angle 1st, LH turn	50 max
Alco lock	without	Immobiliser	with

14 Engine Control			
Speed limitation	89 km/h	Speed limitation legal	90 km/h
Speed limit second	30 km/h	Speed limiter third	without

16 Electrical System			
Short-range radar left-hand side	1 forward+1 rearward looking	Electrical system platform	SESAMM7
Coordinator system	COO11	Alternator charge	180A
Battery	230 Ah	Battery charger	without
Battery system type	single	Battery data module system	BDM2
Battery maintenance type	maintenance-free	Battery position	rear frame end
Battery container size	C	Battery master switch	without
Battery master switch by-pass	without	Batt master switch manoeuvring	without
Alarm system	without	Headlamp type	LED
Headlamp asymmetry	right hand	Head lamp protection	without
Headlamp cleaning	with	Headlamp high located	without
Headlamp levelling	manual	Taillamp position	on bracket
Taillamp type	bulb	Taillamp cable length	without extension
Hazard warning lamp rear	without	Side marker lamps	finally mounted
Spotlamp roof	without	Spotlamp roof additional	without
Dipped beam automatic	with	Dipped beam inclination angle	1 %
Headlamp ventilation	diaphragm	Fog lamp front type	LED 3 diodes
Cornering light	with	Visibility system	CUV3 Extended
Daytime running light	with	Daytime running light function	with LED DRL + position lamps
End outline marker lamp	white	Reflector rear according to ECE-R70	without
Fog lamp front	with	Fifth wheel lighting	white light
Working lamp on rear wall cab top	prepared	Working lamp in cab boarding step FFU	prep left-hand+right-hand
Working lamp side below cab	prepared	Working lamp rear end	without
Beacon	prepared	Horn in front, type	compressed air 118dBA
Reverse alarm	with	Trailer electric coil cable	15 to 15 + 15 to 2x7 pole
Trailer electric connector	1x15 pole	Electric engine heater	without
ADR vehicle designation	without	Forward looking camera	FLC3
Blind spot warning	with	Radar side mounted	left-hand + right-hand
Distance sensor System	DIS3	Bodywork Communication Interface	with
BWE management system	BCI3	BWE control unit configuration	truck
BWE control unit I/O PTO configuration	without	BWE control unit	with



Chassis serial number: 5765886

Chassis type: S 530 A6x2/4NB

BWE expansion unit quantity	without	Switch positions for body work reserved quantity	6 pcs
Bodywork programm switch prep	without	Remote contr engine start	without
Cable harness additional switches	with	Cable harness for bodybuilder	without
Cable harness for bodybuilder frame	without	Cable harness for bodybuilder roof	with
Direction indicator activation	1 bulbs front	ESP Electr.Stability Programme	with, disabling

17 Instruments			
Tachograph	smart 2 STONERIDGE	Tachograph	with
Tachograph data upload	with	Driver identification	without
Adaptive Cruise control	with	Cruise control active prediction speed deviation adjustment	standard+ECO
Lane keep assist	without	Lane change collision prevention	without
Lane departure warning active steering	without	Bluetooth connection	2 pcs
Radio DAB	With	Navigation	With
Tag axle lift trailer button type	display button	Aux symb int driver disp pos 1	towing unit unlocked
Aux symb int driver disp pos 3	5th wh horizontal adjustment	Aux symb int driver disp pos 2	towing unit locked
Aux symb int driver disp pos 4	fifth wheel unlocked	Aux symb int driver disp pos 5	battery saving mode
Aux symb int driver disp pos 6	open door	Aux symb int driver disp pos 7	switched on
Aux symb int driver disp pos 8	switched off	Driver attention support	with
Scania lane departure warning	with	In-vehicle emergency call system	without
Instr panel lower part colour	dark sand	Instrument panel finish	standard
Instrument panel hole 1 equipment	combination module 6+2	Instrument panel hole 2 equipment	switch panel 5
Instrument panel hole 4 equipment	base module 6	Instrument panel hole 5 equipment	switch panel 5
Instrument panel hole 6 equipment	diff module	IP extension hole 11 equipment	without
Emergency braking indication	With	VRU detection rear	With
Vulnerable road user collision warning front	with	Vulnerable road user collision warning side	right-hand
Speed sign information	With	Speed sign information source	camera and map
Speed sign inf audio w setting	default on	Bodywork info in ICL	with
FMS preparation	gateway (interface)	Communicator	C400

18 Cab			
Cab type	CS	Cab length	20 dm
Roof height	high	Cab serial number	5765886
Cab colour grey	Carbon Grey (RAL7024 CM)	Cab colour	Grey
Side panel colour	dark	Front grille upper panel colour	cab colour
Front grille upper ribs colour	cab colour	Front grille lower ribs colour	cab colour
Front grille lower panel colour	cab colour	Boarding step to chassis LH	with
Boarding step panel lower painted	cab colour	Ladder	without
Windscreen	tinted	Rain sensor	with
Door window glass type	laminated	Window, rear wall	without
Window side	without	Sun visor internal type	manual flip-down sun visor
Sun visor, external	with	Sun visor driver door	blind
Sun visor passenger door	without	Door window air deflector	without
Door trim panel type	black leatherette w V8-styling	Air conditioning	with
Auxiliary heating	WTA cab heater 3 kW	Auxiliary heater fuel tank	without
Climate system control	premium	Climate system heating	with
Remote control for climate and infotainment	without	HVAC system configuration	generation 5
Cab socket 230V	without	Auxiliary cab cooler	with
Auxiliary cab cooler on roof	without	Adaptive cruise control AICC deactivation speed	0 km/h
Cab suspension	air comfort	Cab tilting	mechanical
Roof hatch	without	Alarm system	without
Frequency remote lock	433 MHz	Number of keys/remotes	two
Roof rail	long	Roof air deflector height	without
Side air deflector length	53 cm	Air deflector side material	thermoplastic
Seat upper backrest adjustable driver	with	Seat ventilation driver side	with
Seat category driver side	premium	Driver's seat lumbar support	with
Seat upholstery driver side	V8 leather black w red stitch	Seat adjustable shock absorber driver side	with
Passenger seat lumbar support	with	Seat category passenger side	premium
Seat upper backrest adjustable passenger	without	Seat ventilation passenger side	without
Seat adjustable shock absorber passenger side	with	Seat upholstery passenger side	V8 leather black w red stitch
Red coloured seat belts	without	Seat belt pretensioner	without
Bed lower	800 mm, fixed	Bed lower, mattress pad	without
Bed lower, mattress	bonell	Insert tray under lower bed	driver side+passenger side
Bed upper	without	Bed safety net	without
Seat engine tunnel	without	TV preparation	without
USB charging port rear wall	with	CB radio	prep 12V with speaker
Horn on cab roof	prepared	Mudflap length front	90 mm
Front mudguard size	675 mm	Front mudguard indentation	without



Chassis serial number: 5765886

Chassis type: S 530 A6x2/4NB

Front mudguard rear part length	725 mm	Front mudguard rear part high ground clearance	without
Front wheel arch trim panel size	565 mm	Mudflap rear	with
Rear mudguard lateral location	outer	Mudguard second front axle	without
Mudguard rear	with	Mudflap length rear	276 mm
Rear mudguard, execution	high top	Splash guard rear material	plastic
Spray-suppression according to EU 109/2011	with	Frontview mirror	electrical adjusted + heating
Rear view mirror heating	with	Rear view mirror type	A
Rear view mirror glass type driver side	spherical	Rear view mirror glass type passenger side	spherical
Rear view mirror electrically adjustable	passenger+driver side	Close-proximity mirror	electrical adjusted + heating
Wide angle mirror	driver+passenger side	Microwave oven	without
Coffee maker	without	External storage compartment	driver+passenger side
External storage below cab	driver+passenger side	Storage rear lower on driver side	refrigerator
Storage rear lower passenger side	drawer	Storage compartment above door	with
Roof shelf rear wall	with	Storage side panel	left and right hand side
Storage shelf on rear wall FFU	2 pcs		

19 Complementary Equipment			
Fifth wheel	JOST JSK37C-Z 150	Fifth wheel position	-760 mm
Fifth wheel category	fixed, plate-mounted	Mounting plate	40 mm, D-value max 152kN HD
Catwalk	without	ACL automatic chassis lubrication	without
Dimension JA/BEP L020	715 mm	Trailer electric connector	1x15 pole
Trailer connection coiled hoses type FFU	red/yellow ISO	Underrun beam according to AR regulation	without
Rescue equipment except fire extinguisher	with	Hose for tyre inflation	without
Spare wheel carrier	without	Smoke detector	without
Fire extinguisher	1 x 3 kg	Jack	without
Warning triangle	1 pcs	Emergency hammer	without

20 Load Carrying Bodywork			
Tail lift	without	Refuse packer step	without
Wet kit equipment	without		

Certificate			
Advanced Emergency Braking E4 - 131R - 010008 EXT.19	AirDrag CO2 Declaration e4*2017/2400*2019/318*P*0058*01 Corr. Rev.	Alcohol interlock installation facilitation in moto r vehicles e9*2021/1243*2021/1243*11001*01 Corr. Rev.	Anti-theft systems E4*18R03/04*0208*07
Audible warning devices (Signal horn) E4 - 28R - 000684 EXT.05	Axle CO2 Declaration e4*2017/2400*2019/318*L*0032*01 Corr. Rev.	Blind Spot Information Systems E9*151R00/04*1001*02	Brakes E4 - 13R - 112655 EXT.23
Cab Strength E4 - 29R - 030117 EXT.21	Coupling Devices E4 - 55R - 010792 EXT.27	Cyber Security E4*155R00/02*0017*00	Devices for Indirect Vision E9*46R04/09*16336*01
Driver drowsiness and attention warning system s (DDAW) e4*2021/1341*2021/1341*00009*01 Corr. Rev.	Electromagnetic compatibility (EMC) E9*10R06/02*16677*21	Engine CO2 Declaration e4*2017/2400*2019/318*E*0653*01 Corr. Rev.	Engine Emissions e4*595/2009*2019/1939E*0138*05 Corr. Rev.
Engine Emissions E4*49R06/08/D*0570*04	Engine Power E4*85R00/12*1604*03	Engine Smoke E4*24R03/05*1247*00	External Projections E9*61R00/03*1089*07
Front Under Run Protection E4 - 93III R - 000089 EXT.12	Fuel Tanks E9*34R03/02*1369*05	Headlamp Cleaners E4 - 45R - 010069 EXT.05	Heating Systems E9*122R00/06*1367*04
Intelligent Speed Assistance e9*2021/1958*2021/1958*11011*03 Corr. Rev.	Lane Departure Warning System (LDWS) E4 - 130R - 000010 EXT.16	Lighting E4 - 48R - 060614 EXT.17	Masses and Dimensions e4*1230/2012*2019/1892*0363*33 Corr. Rev.
Moving Off Information System(MOIS) E9*159R00/02*1001*02	Noise E4 - 51R - 032533 EXT.07	Registration Plate Space e4*1003/2010*2015/166*0184*05 Corr. Rev.	Reversing Detection System E9*158R00/01*1005*01
Safety Belt E4 - 16R - 080484 EXT.16	Safety Belt Anchorages E4 - 14R - 090657 EXT.14	Safety Glazing E9*43R01/09*1357*04	Seats E4 - 17R - 090582 EXT.14
Software Update E4*156R00/00*0015*02	Speed Limiter E4*89R00/03*0069*20	Speedometer E9*39R01/02*1834*01	Spray Suppression System e4*109/2011*2015/166*0137*09 Corr. Rev.
Steering E4 - 79R - 040651 EXT.21	Symbols E9*121R01/06*1402*07	Tachograph e5*165/2014*980/2023*0002*09 Corr. Rev.	Towing Devices e4*1005/2010**0177*10 Corr. Rev.
Transmission CO2 Declaration e4*2017/2400*2019/318*G*0634*02 Corr. Rev.	Type Plate e4*19/2011*249/2012*1158*17 Corr. Rev.	Tyre CO2 Declaration e13*2017/2400*2017/2400*T*0171*00 Corr. Rev.	Tyre CO2 Declaration e13*2017/2400*2019/318*T*0262*00 Corr. Rev.
Tyre Pressure Monitoring System (TPMS) E9*141R01/02*1057*03	Tyres E4*142R01/01*0033*06	Vehicle access and manoeuvrability e9*130/2012*130/2012*31006*05 Corr. Rev.	Whole Vehicle Type Approval e4*2018/858**00100*12 Corr. Rev.

Corporate contract			
Description	TP - Truck Powertrain	Status	Active
Start Date	2025-04-19	End Date	2032-04-18

Modifications	
Change orders	803540 - Description missing