

BP Series
Briquetting Press



- Maintenance smart design
- Available for steel, aluminum, copper, zinc, lead etc.
- Centrifuging and shredding solutions for chips
- Optional briquette length adjustment system



	BP	60	80 ECO	80	100	120	160	200
Briquette Diameter	mm	60	80	80	100	120	160	200
Main Cylinder Power	ton	100	150	220	315	400	600	850
Capacity (Steel, Cast) <	ton/h	0.15	0.4	0.8	1.3	2.6	6	12
Capacity (Copper) <	ton/h	0.20	0.6	1	1.5	2.7	7	13.5
Capacity (Aluminum) <	ton/h	0.05	0.09	0.3	0.5	0.8	2.3	4
Cycle Time	s	12	12	12	12	12	12	12
Motor Power	kw	22	30	30	55	75	150	180
Machine Weight	ton	3.5	4	6	12	13	28	60
Footprint	m	1.7x2	2x2.2	2x2.7	2.4x3.5	2.4x4	3x6.5	11x10

- Density : Steel-Cast <= 5.5 kg/dm3, Copper <= 7.0 kg/dm3, Aluminum <= 2.4 kg/dm3
 - Working pressure is 300 Bar . BP 60 working pressure is 220 bar max.

- Capacity depends on material