



Technical Data

Model: DPX-19806 - Perkins 1104C-44TAG2 - 110 kVA AJ- 110P

Prime power	kva	100
	kw	80
Standby power	kva	110
	kw	88
Rated voltage line to line	V	230/400
Rated current	A	144
Maximun sound level	dB@7m	72

Engine-Perkins

Model		1104C-44TAG2
Aspiration		Four-stroke, water-cooled, In line, Turbo charged, air to air
Fuel system		Direct injection
No. cylinders		4
Displacement	L	4,41
Bore*Stroke	mm	105x127
Compression ratio		18.2:1
Rated speed	r/min	1500
Governor		electrical
Engine size	mm	1259x721x966
Engine wet weight	kg	550
Fire order		1-3-4-2
Start Motor	V	12
Rotation		Anti-clockwise, viewed on the flywheel

Air Inlet

Air inlet		mounted air filter
-----------	--	--------------------

Fuel System

mechanical governor		cassette type fuel pump
fuel filter		Ecoplus fuel filter

Fuel System

110% load(Standby power)	L/h	24,9
100% load(Prime power)	L/h	22,6
75% load(Prime power)	L/h	17,1
50% load(Prime power)	L/h	11,2
Fuel capacity	L	200

Lubrication System

Oil capacity	L	8
--------------	---	---

Cooling System

Total coolant capacity	L	12,6
------------------------	---	------

Standard Features

Engine(Perkins ENGINE)	●
Radiator 50°C max,fans are driven by belt	●
12V charge alternator	●
Alternator: single bearing alternator IP23	●
insulation class H/H	●
Standard auto control system	●
Main line circuit breaker / ACB	●
Base fuel tank	●
12V batteries, rac and cable	●
Exhaust system(Ripple flex exhaust pipe)	●
Exhaust siphon, flange, muffler	●
User manual	●
Battery charge	●

Options

Water heater	○
Alternator heater	○
One set of air filter, fuel filter, oil filter	○
PMG	○
Water oil separator	○
Daily fuel tank	○
Remote control panel	○
Automatic transfer switch/ATS	○
Switch box	○
Standard: ●	Options:○

Alternator

Model		TAL-A44-D
Alternator Brand		Leroy Somer
Phase		3
Voltage	V	230/400
Wiring Type		12 wires
Bearing		1
Power factor		0,8
Frequency	Hz	50
Prime power	KVA	100
Exciter Type		Brushless, self-excitation
Voltage regulation	%	±0.5
Protection Grade		IP 23
Insulation grade		H


Controller-Deepsea

Model DSE 6120

7 configurable digital inputs
Built-in governor and AVR control
Base load (kW export) functionality
Mains (utility) de-coupling protection
Generator power (kW, kVA) monitoring
Overload (kW & kV Ar) protection
Emergency stop
Start failure



Unit Dimensions(Basic unit)

		
L*W*H	+/- mm	2700x1050x1250
Weight	+/- kg	1.320

Warranty

Perkins Engine

12 months from date of purchase or 1000 hours.

Generator

12 months from date of purchase or 1000 hours



YOUR INTERNATIONAL PARTNER FOR
NEW AND USED GENERATOR SETS