

PRODUCT SAFETY DATA SHEET

Océ Display Graphics Systems

13251 Delf Place
Building #406
Richmond, British Columbia.
Canada V6V 2C3

telephone 604 273 7730
For safety questions contact the Product Safety Coordinator
of your local Océ organisation



Number: 13x00DGS
Date: Aug 2018

Model(s)	Océ Arizona® 1340 GT, Océ Arizona® 1360 GT, Océ Arizona® 1380 GT Océ Arizona® 1340 XT, Océ Arizona® 1360 XT, Océ Arizona® 1380 XT with Option RMO										
Description Process speed	Graphics Print Systems Océ Arizona® 13x0 GT Up to 33.6 m²/hr Océ Arizona® 13x0 XT Up to 35.0 m²/hr Option RMO - Roll Media Printing Up to 25.6 m²/hr.										
Dimensions: * width * depth * height * weight	Océ Arizona® 13x0 GT 4.656m 2.0m, 2.285m w/Option Table, 0.88m/Gantry, 1.3m 856 kg, with Option 1106kg	Océ Arizona® 13x0 XT 4.656m 3.83m, 4.12m w/Option 1625 kg, with Option 1800kg									
Electrical data: * voltage * current-rated * building fuse Mains connection Safety class Protection class EMC Class Battery Type (weight)	Océ Arizona® 13x0 GT 200 - 240V 50/60Hz 8A Inlet 1 and 3A Inlet 2 20A USA and 16A EU Cable with plug I (IEC 61140) Protective earth connection IPX0 (IEC 60529) Class A (according to EN64000-6-4) CR2032 (3.3 grams, present on CPU)	Océ Arizona® 13x0 XT 15A Inlet 1 and 3A Inlet 2									
Energy consumption: * off * ready * maximum	Océ Arizona® 13x0 GT 0 W 200 W 1700W Inlet 1 and 500W Inlet 2	Océ Arizona® 13x0 XT 0 W 200 W 3450W Inlet 1 and 500W Inlet 2									
Noise emission ¹ : * Sound pressure level (at operator position) Heat emission Radio interference Radiation Chemical emission: * dust * ozone * TVOC	Less than L _{pA} = 70dB (A) Not applicable Complies with Directive 2004/108/EC and FCC rules and regulations, part 15 Class A. Not applicable <table><tr><td>Emission (mg/h)</td><td>Concentration (mg/m³) ¹</td></tr><tr><td>8.6</td><td>0.000735</td></tr><tr><td>0.0</td><td>0.0</td></tr><tr><td>340</td><td>0.28</td></tr></table>			Emission (mg/h)	Concentration (mg/m³) ¹	8.6	0.000735	0.0	0.0	340	0.28
Emission (mg/h)	Concentration (mg/m³) ¹										
8.6	0.000735										
0.0	0.0										
340	0.28										
Recommended room ventilation	≥ 1200 m³ per hour. For heat evacuation extra ventilation may be necessary.										
Consumables	This apparatus is suitable for IJC357 Ink Materials										
Additional safety information	UV inks can be harmful if not properly handled. Follow the guidelines in the User Guide carefully in order to ensure maximum safety.										
¹ average concentration, additional to background, calculated for a daily volume of continuous prints during a work time of 8 h at recommended minimal room volume and room ventilation <i>Under normal conditions of use concentrations are considered to remain around or below above concentrations. Concentrations are a best estimate and have been calculated from concentration measurements performed under practical conditions in a room with a volume of 195 m³ and a ventilation rate of 6/h.</i>											
CE-Compliance	Approval according to Machinery Directive 2006/42/EC	Approval according to standard UL73 and CSA 22.2 No. 68-92	Approved according 2014/30/EU ²								
			² Report available on request.								

This safety data sheet has been compiled to the best of our knowledge as a compact guide to safe handling of this product. We reserve the right to revise safety data sheets as new information becomes available. It is the user's responsibility to determine the suitability of this information for the adoption of safety precautions as may be necessary and to contact the company to make sure that this sheet is the latest one issued. If and in so far as limitation of liability is permitted under the applicable laws, we do not accept liability for any inaccuracy that may occur in this information.