

Because we care

ADK V 600

MOBILE ACCUMULATOR-DRIVEN SUCTION FRAME



Flexible accumulator-driven suction frame for mobile use


- Self-contained, accumulator-driven manipulator for handling glass panes and similar plates
- Stepless tilting via hand-operated hydraulic
- Continual manual rotation
- Low own weight


- Two-circuit-vacuum system manufactured to European Standards EN 13155
- Minimal maintenance requirements
- Ergonomically arranged control elements

Versatile application possibilities

Various modifiable suction cup and connector positioning options made easy via socket pins (without tools).

With suction bar for narrow panes Ø300





Practical supplementary equipment

Extra suspension (interchangeable) enabling the ADK to be used for façade glazing between the scaffolding and the façade of the building



Transport box for the manipulator ADK plus accessories





Fork-lift truck fixing device



TECHNICAL DATA	ADK V 600
Application	Self-contained in chain or wire rope hoist, in hall or mobile crane
Safe working load	600 kg
Rotation of load	Manually, continual, locking every 45°
Tilting of load	Stepless 0 – 90° by hand-operated hydraulic
Suctions cups	6 pieces, Ø 300 mm
Vacuum generation	Vacuum pump
Own weight	90 kg
Battery	12 V / 7,2 Ah, enough for approx. 150 x sucking
Battery charger	230 V
Dimensions of suctions frame	Variable, using combinations of connectors and suction cups
Safety device	Visual indicator





www.glaston.net