



TYPE OF MACHINE :

CNC jig grinding machine

STOCK N°

90123

BRAND

HAUSER

MODEL

S40-400

YEAR

1996

LOCATION

**73240 St-Genix-les-Villages,
FRANCE**

[DIRECT LINK](#)





TECHNICAL CHARACTERISTICS

Stroke X axis	650 [mm]
Max. Stroke speed X axis	4000 [mm/min]
Working feed X axis	0 - 1800 [mm/min]
Stroke Y axis	450 [mm]
Working feed Y axis	0 - 1800 [mm/min]
Stroke Z axis	130 [mm]
Min. Stroke speed Z axis	0.5 [mm/min]
Max. Stroke speed Z axis	12000 [mm/min]
Stroke frequency Z axis	max. 4 [Hz]
Stroke W axis	500 [mm]
Planetary speed C axis	5 - 250 [rpm]
Max. Stroke speed W axis	800 [mm/min]
Stroke U axis (radial feed)	5.5 [mm]
Distance between columns	750 [mm]
Table length	770 [mm]
Table width	630 [mm]
Clearance between grinding motor and table	585 [mm]
Max. load on table	500 [Kg]
Supply voltage	400 [V]
Weight	4550 [Kg]

The information on this page has been obtained by the best of our ability. Therefore, its accuracy can not be guaranteed



ADDITIONAL INFORMATION

EQUIPMENT INCLUDED:

x1 HI-CUT pack including:

- work area protection
- exhaust system with electrostatic air filter
- fire protection system (to be assessed by a qualified body)
- HTG-RWS-60 automatic belt filter cooling unit

x1 MSS (Multi-Sensoric System) tool detection device
x1 CBN dressing unit with HF drive for automatic dressing of CBN grinding wheels (ceramic bond and synthetic resin)
x1 T16 grinding turbine - speed: 160,000 rpm - reference: 164225
x1 turbine support with filter for use with T10 and T16 turbines - reference: 166497
x1 60S-TC grinding motor, speed 9000 - 60000 [rpm], for SK20 collets - part number: 208450
x1 intermediate plate for aligning motors and turbines - reference: 192940
x1 centring watch holder for grinding motor rotor - reference: 191790
x15 wheel holder cleats
x1 cable for grinding motor
Various tools
Full documentation

The information on this page has been obtained by the best of our ability. Therefore, its accuracy can not be guaranteed























