HP DesignJet Z6 PostScript Printer series

High-definition prints, fast and secure. More quality with fewer inks.





PRECISE—Clearly distinguish subtle details

- Read details more clearly and see high-contrast color with new high-definition HP printheads.
- No need for light inks with HP's dual drop technology.
- Get smooth gradients, even for challenging color combinations, with HP Pixel Control.
- Work with water- and fade-resistant prints, indoors and out, with HP Vivid Photo Inks.¹

FAST—Work without delays

- Handle even the most complex files with powerful processing architecture and the Adobe PDF Print Engine.²
- Cut maps to different sizes in fewer steps with the first printer including an integrated vertical trimmer.³
- Print up to 20% faster⁴ with 2400 nozzle-perinch, high-definition HP printheads.
- Spend less time on media changes and adjustments with dual roll support and automatic roll switching.³

SECURE—Protect your work and your information

- Protect printers/data from unauthorized access with HP Secure Boot, whitelisting, and encrypted hard disk.
- Protect documents, preserve confidentiality with authentication solutions like PIN printing, card readers.⁵
- Secure your printers with HP JetAdvantage Security Manager; manage your fleet remotely with HP Web Jetadmin.

For more information, please visit http://www.hp.com/go/designjetZ6

Dynamic security enabled printer. Contains technology that may prevent cartridges with non-HP chips or circuitry from working now or in the future. More at: http://www.hp.com/learn/ds

¹ Performance may vary based on writing system differences. Print permanence estimates by HP Image Permanence Lab based on the same formulation of HP Vixid Photo Inks used with the HP DesignJet Z6200 Photo Production Printer, using 6 inks. Water resistance performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. Display permanence rating for interior displays/away from direct sunlight by HP Image Permanence Lab on a range of HP media. For more information, see http://www.HPLEMedia.com/printpermanence
² The Adobe PDF Print Engine (APPE) is Adobe's high speed, high fidelity print platform. Version 4 extends APPE's leading edge for print reproduction with new performance efficiencies and breakthrough rendering features. APPE 4 enables printers to increase workflow efficiency and capitalize on the profit potential of innovations in inkjet print technology. To learn more, visit https://www.adobe.com/products/pdfprintengine.html
³ Vertical trimmer only.
⁴ Based on internal HP testing. Up to 20% faster printing compared to the HP DesignJet Z2600 PostScript® Printer and HP DesignJet Z2600 PostScript® Printer and HP DesignJet Z5600 PostScript® Printer. May vary depending on print mode and media type.

⁴ Based on internal HP testing. Up to 20% faster printing compared to the HP DesignJet Z2600 PostScript[®] Printer and HP DesignJet Z5600 PostScript[®] Printer. May vary depending on print mode and media type.
⁵ Card reader functionality enabled through optional third-party solutions.

Technical specifications

Rest: 6.6 m ¹ /tr on plasmeda Rest: 7.3 m ¹ /tr on opsaymeda Normat: 18.8 m ¹ /tr on opsaymeda Rest: 7.3 m ¹ /tr on opsaymeda Fast: 8.6 m ¹ /tr on opsaymeda Rest: 7.3 m ² /tr on opsaymeda Print resolution Up to 2400 n 1200 optimmed dpi Technology HP thermal indjet Margins Rest: 5.4 m ² /s 5.5 mm forderlets on selected media ³ , or on all media with V-Timmer ⁴) Steep: 5.4 m ² /s 5.5 mm forderlets on selected media ³ , or on all media with V-Timmer ⁴) Technology HP thermal indjet Margins Steep: 5.4 m ² /s 5.5 mm forderlets on selected media ³ , or on all media with V-Timmer ⁴) Printhead Juite second (Juite Second	Print speed	24-in:
44.9. 44.9. Fast. 6.1 min production reduction Fast. 6.1 min production reduction Min production Wit production Returned triade Min production	Philit Speed	Fast: 66.9 m²/hr on plain media Normal: 15.2 m²/hr on coated media
Batel Stand Print Coupling Print Coupling Print Coupling Print Prin		
Pint resolution Up 12 400 x 1200 spinneed dpl Technology HP Terminal H&pint Relig Se S x 17 X S x S mm Boodreless on selected media ¹ , or on all media with V-Trimme ⁴) State S x 17 X S x S mm Boodreless on selected media ¹ , or on all media with V-Trimme ⁴) State S x 17 X S x S mm Boodreless on selected media ¹ , or on all media with V-Trimme ⁴) Print House 211 2 per color; 12.672 in total Development Print House S with 0 routs (action 0 Print House S with 0 routs (action 0 Print House M M Color, 12.672 in total D.02 mm BOT adversable (9 1200 dp) Stort-Herm Num Hauk MM D.02 mm BOT adversable (9 1200 dp) Stort-Herm Num Hauk MM D.02 mm BOT adversable (9 1200 dp) Stort-Herm Num Hauk MM D.02 mm BOT adversable (9 1200 dp) Stort-Herm Num Y MM H mint 2-5 D ¹ Media Single-roll Roll Feed, media output toin, automatic horizontal cutter Daal-roll File Maus adversable (9 120 k FE mm Advers2 20 k 12 FE mm Botter 12 FE mm Advers2 721 to 11 10 k mm Advers2 721 to 11 10 k mm Heard House X Advers Adversable (9 120 k FE mm Advers2 20 k 2 FE mm Botter 12 FE mm Gardend House X Adversable (9 120 k FE mm Adversable (1000Base - 110 k FE mm Gardend House X Adversable (9 120		Fast: 80.5 m²/hr on plain media Normal: 18.8 m²/hr on coated media
Retrology LP Thermal Inkjet Wargin Bill 5: 55: 55: 55: 0000 Name: Sci 21: 25: 55: 55: 0000 Description of Sci 2000 Name: Sci 21: 25: 25: 55: 0000 Description of Sci 2000 Printhead 20: 20: 20: 20: 20: 20: 20: 20: 20: 20:	Print resolution	
Harges ER: 5: 5: 5: 5: 5: 5: 5: 5: 5: 5: 5: 5: 5:		
Sheet: X 7 X 5 X 5 mm ik pipes Paper-Nesdel ink dop 77.3 pl dual-dop weight (N.C. PR): 6 pl single-drop weight (C.C. MA) Purifiends 3 universal printhesids (all for all colors) Printhesids 11.2 per color. 12.6 2 Pl in total Damman line worth 0.02 mm (PCP adversable (P1 200.0pl) Sharman line worth 0.02 mm (PCP adversable (P1 200.0pl) Shart-form color stability 1 at 200.00 in lises than 5 minute? Line system Average < 0.5 dE2000.995% of colors < 1.4 dE2000 ⁷ Shart-form color stability 1 at 200.00 prints Marce yood density 4 tranu2.5 D ² Mexing 0.02 eraft high adversable (P1 200.0pl) Shart-form color stability 1 at 200.0pl Marce yood density 4 tranu2.5 D ² Marce yood density 4 tranu2.5 D ² Marce yood density 4 tranu2.5 D ² Marce yood density 2 tranu2.5 Pl 20 high Shart-form density 2 tranu2.5 Pl 20 high Marce yood density 2 tranu2.5 Pl 20 high Shart-form density 2 tranu2.5 Pl 20 high Marce yood density 2 tranu2.5 Pl 20 high		
nik forg. 7/3 pl Audi-drog weight M.C., PR2, 6 pl Single-drog weight K.C.G. MA3 Furtheads 2014 Furtheads 2014 Dev code and def or all colors! Furtheads 2014 Dev code 112.627: In total 2012 Dev code 112.627: In total 2012 Dev code 2012 Dev code 2012 Dev code 2012 Dev code Wintrum inter with 0.02.07.mm IDGF addressable @ 1200 dpl Competency of the set		Sheet: 5 x 17 x 5 x 5 mm
Printheads 3 universal printheads heal for all colorsd Printhead mozdes 2112 per color; 12.672 to total Interacturary 0.01% Meanum line width 0.02 mm (PDF addressable (#) 1200 dpl) Short-term color stability 4 to #2000 heas than 5 minutes? Meanum line width 0.02 mm (PDF addressable (#) 1200 dpl) Media Meanum line width Max optical denoisty 4 to min/2.5 p7 Media Single-roll: Roll Feed, rear sheet feed, media output bin, automatic horizontal outer and vectoral torine feed, media output bin, automatic horizontal outer and vectoral torine data and per colors and a stability Roll size 24-in: 270 to 610 rtm 24-in: 270 to 610 rtm 44-in: 210 x 271 to 610 rtm Sheet size 24-in: 270 to 610 rtm 24-in: 270 to 610 rtm 44-in: 210 x 271 to 110 to 167 rtm Sheet size 24-in: 270 x 271 to 110 to 167 rtm Sheet size 24-in: 270 x 271 to 110 to 167 rtm Sheet size 24-in: 210 x 271 to 110 to 167 rtm Sheet size 24-in: 210 x 271 to 110 to 167 rtm Sheet size 24-in: 210 x 271 to 110 to 167 rtm Sheet size 24-in: 210 x 271 to 110 to 167 rtm		5 5
Printhead nozzles 2112 per color; 12,6/2 in total Line accuracy 0.01% ⁵ Marmuni Ine width 0.02 mm (PDF addressable © 1200 dp0 Shart-term colar stability <1 dt2000 in less than 5 minutes?		
Line accuracy ±0.18 ³ Minimum Ine width 0.02 mm PDF addressable @ 1200 dp0 Minimum Ine width 4.1 dE2000 n less than 5 minutes? Long-term point along minutes of the second structure for the second structure for the second structure for the second structure for the second structure of the second structure of the second structure for the second struct		•
Minimum line width 0.02 mm (PDF addressable @ 1200 dp) Short -term color stability 4.1 dt2000 hess than 5 minutes? Expert -term color stability 4.1 dt2000 hess than 5 minutes? Max optical devisity 4.1 dt2000 hess than 5 minutes? Max optical devisity 4.1 min2.5 D ⁷ Meda Stability Stability 5.0 dt2000, 95% of colors < 1.4 dt2000 ⁷ Meda Stability Stability 5.0 dt2000, 95% of colors < 1.4 dt2000 ⁷ Meda Stability 5.0 dt2000, 95% of colors < 1.4 d	Printhead nozzles	2112 per color; 12,672 in total
Short-term color stability < 1 dE2000 in less than 5 minutes?	Line accuracy	±0.1% ⁵
Long-term print-to-print Average < 0.5 dE2000, 95% of colors < 1.4 dE2000 ⁷ Media Handling Single-roll: Roll Reet, rear sheet feed, media output bin, automatic horizontal cutter Dud-effect: No automatic roll feeds, smart roll-switching, top sheet, teed, media output bin, automatic horizontal cutter Dud-effect: No automatic roll feeds, smart roll-switching, top sheet, teed, media output bin, automatic horizontal cutter Dud-effect: No automatic roll feeds, smart roll-switching, top sheet, teed, media output bin, automatic horizontal cutter Dud-effect: No automatic roll feeds, smart roll-switching, top sheet, teed, media output bin, automatic horizontal cutter Dud-effect: No automatic roll feeds, smart roll-switching, top sheet, teed, media output bin, automatic horizontal cutter Dud-effect: No automatic roll feeds, roll roll roll roll roll roll roll rol	Minimum line width	0.02 mm (PDF addressable @ 1200 dpi)
repeatability Max optical density Max optical	Short-term color stability	< 1 dE2000 in less than 5 minutes ⁷
Media Single-roli: Roll feed, rear sheet feed, media output bin, automatic horizontal cutter Binding Single-roli: Roll feed, rear sheet feed, media output bin, automatic horizontal cutter Boll size 24:10: 279 to 1118-mm Madimum roll diameter 135 mm Sheet size 24:41:: 279 to 1118 × 1676 mm Sheet size 24:41:: 279 to 1118 × 1676 mm Sheet size 24:41:: 47.3, A2, A1 Grammage 80 to 500 g/m² Thickness Up to 0.6 mm Applications Banness: bribition and event graphics; Light boxes - film; Maps; Orthophiotos; Point of sale/display; Posters Memory 128 GB (virtual) ⁶ Hand disk 500 GB self-encrypting ConnectMity Itterfaces Ittal disk 500 GB self-encrypting ConnectMity Apple Adobe PostScript 3, Adobe PD 1.7, TEF, JPES, CALS G4, HP-GU2, HP-RTL Phinting paths Apple Adobe PostScript 3, Adobe PD 1.7, TEF, JPES, CALS G4, HP-GU2, HP-RTL Phinting paths Apple Adobe PostScript 3, Adobe PD 1.7, TEF, JPES, CALS G4, HP-GU2, HP-RTL Phinting paths Apple Adobe PostScript 3, Adobe PD 1.7, TEF, JPES, CALS G4, HP-GU2, HP-RTL Phinting paths Apple Adobe PostScript 3, Adob		Average < 0.5 dE2000, 95% of colors < 1.4 dE2000 ⁷
Handling Single-roll: Roll feed, rear sheet feed, media output bin, automatic horizontal cutter and vertical immore (usal life 2-sense printer-qualited media, including most canvas) Roll size 24-in: 279 to 610-mm 44-in: 279 to 610-mm 44-in: 279 to 10118-mm Maximum roll diameter 135 rm Sheet size 24-in: 279 to 610-mm 44-in: 210 x 279 to 610 f676 mm 44-in: 210 x 279 to 610 mm 44-in: 210 x 279 to 610 f676 mm 44-in: 210 x 279 to 700 f676 mm 	Max optical density	4 L* min/2.5 D7
Dual-roll: Two automatic roll feeds, smart roll-switching, top sheet feed, media upput bin, automatic horizontal cutter and vertical tormme (total HP 2-series printer-qualited media, including most canves) Roll size 24-in: 279 to 610 - mm 44-in: 279 to 610 - mm 44-in: 210 x 279 to 118-mm Maximum roll dameter 135 mm Sheet size 24-in: 210 x 279 to 118 - for mm 44-in: 210 x 279 to 118 - for mm 44-in: 210 x 279 to 118 - for mm Grammage 80 to 500 g/m ² Thickness Up to 0.8 mm Application5 Banners, Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display. Posters Memory 128 GE (Writual) ⁶ Hand disk 500 GB self-encrypting Connectivy Adobe PostScript 3, Adobe POF 1.7, THF; JPEG, CALS GA, HP-GL/2, HP-AFTL Printing paths Adobe PostScript 3, Adobe POF 1.7, THF; JPEG, CALS GA, HP-GL/2, HP-AFTL Printing paths Apple AiPrint, direct printing from USE flash drive for macCS, HP driver for macCS, HP driver for Windows, AP adobe Printing paths Apple AiPrint, direct printing from USE flash drive, enall printing, HP Citek, HP driver for macCS, HP driver for Windows, AP adobe Printing paths Paster and PostScript 3, Adobe POF 1.0, 11.11, ZP WP betachmic morphatice, HP driver for macCS, HP driver	Media	
44-in: 279 to 1118-mm Maximum roll dameter 135 mm Sheet size 24-in: 210 x 279 to 101 k1 k1676 mm 44-in: 210 x 279 to 1118 x 1676 mm Standard sheets 24-in: A1, A3, A, A1, 1 44-in: A3, A, A, A1, A0 Grammage 80 to 500 g/m ³ Thickness Up to 0.8 mm Applications Bannes: Subhition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (virtual) [®] Taid disk 500 GB self-encrypting Connectivity Interfaces (ligable Ethernet (1000Base-T) (802.3, 802.3u, 802.3u); Hi-Speed USB 2.0 certified interface for direct printing from USE flash drive print languages Adobe PostScript 3, Adobe POF 1.7, TIFF, IPEG, CALS GA, HP-GL/2, HP-RTL Phinting paths Apple AliPhrit, direct printing from USE flash drive, enall printing, HP Click, HP driver for macOS, HP driver for Windows and daobe Drivers Raster and PostScript 3, Adobe POF 1.7, TIFF, IPEG, CALS GA, HP-GL/2, HP-RTL Phinting paths Apple AliPhrit, direct printing from USE flash drive, enall printing, HP Click, HP driver for macOS, HP driver for Windows and daobe Drivers Raster and PostScript 3, Mode Adobe Security features HP Secure Boot, Whiteisting, Role Based Access Control, SMMPv3, HTTPS, Secure-IPR, IPSec/Frievall, Certificates maragement, 802.11, T15.10/1.11/2, HP Web Jetadmin compabible, HP JetAdvantage Security Manager compabible, Secure D	Handling	Dual-roll: Two automatic roll feeds, smart roll-switching, top sheet feed, media output bin, automatic horizontal cutter
Sheet size 24-in: 210 x 279 to 510 x 1676 mm Sheet size 24-in: 210 x 279 to 510 x 1676 mm Standard sheets 24-in: 240 x 279 to 510 x 1676 mm Grammage 80 to 500 g/m² Trickness Up to 0.8 mm Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (withual) [®] Hard dsk 500 GB self-encrypting Connectivity Gigabit Ethernet (1000Base-1) (602.3, 802.3u, 802.3u); Hi-Speed USB 2.0 certified interface for direct printing from USE flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RT. Printing paths Apple AMPinit, direct printing from USE flash drive, email printing. HP Click, HP driver for macOS, HP driver for Windows; and macOS Drivers Raster and PostScript 13, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HD-GL/2, HP-AT. Printing paths Apple comming support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for IOS and Android HP SmartStream Drivers Raster and PostScript 13, and above Security features HP Secure Bost, Wintel King, Rule Based Arcses Control, SMMPU3, HTTPS, Secure-IPP, IPsec/Flewall, Certificates maragement, 802.27, TIS 1.01, 17, 17, HP Web Jatahnin compatible, HJ JacAdamtage Security Manager compatible, Secure Disk ease (100.02 220.22 24M). Secure File	Roll size	
44-m: 21 to x 27 to 111 8x 1676 mm Standard sheets 24-in: A4, A3, A2, A1, A0 Grammage B0 to 500 g/m² Thickness Up to 0.8 mm Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 G6 (virtual) [®] Hard disk 500 G8 self-encrypting Connectivity Interfaces figabit Ethermet (1000Base-T) (802.3, 802.3u, 802.3ub; Hi-Speed USB 2.0 certified interface for direct printing from USE figabit Ethermet (1000Base-T) (802.3, 802.3ub; Hi-Speed USB 2.0 certified interface for direct printing from USE figabit Ethermet (1000Base-T) (802.5, HP ChLZ, HP-RTL Native print Languages Adobe PostScript 3, Adobe POF 1.7, TIFL /PEG, CALS G4, HP-GLZ, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Cick, HP driver for macOS, HP driver for Windows and macOS PDF driver for Unixus, printing Role Based Access Control, SMMPA3, HTTPS, Secure-IPP (Psec/Firewall, Certificates margement, 802.1 X, TIS 1.0 / 1.1 / 1.2, HP Web betadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD S22.0 22-M). Secure File erase, self-encrypted HD0, PNI printing Stephong 24-in: 1293 X 695 X 998 mm 44-in: 1802 X 695 X 998 mm 44-in: 1802 X 695 X 998 mm Stephong 97-132 kg What's in the box HP Desig	Maximum roll diameter	135 mm
44-in: Ad, A3, A2, A1, A0 Grammage 80 to 500 g/m ³ Thickness Up to 0.8 mm Applications Bannes; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (virtual) ⁸ Mark 500 GB self-encrypting Connectivity Interfaces flash drive flash drive Native print languages Adobe PostScript 3, Adobe PD 1.7, TIFF, JPEG, CALS GA, HP-GL/2, HP-RTL Printing paths Apple Arbitring from USE flash drive, email printing, HP Click, HP driver for Windows, HP driver for Windows and macOS PDr driver for Unux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for IOS and Android HP Smart Stream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows B and above Security features Security features HP Secure Boot, Whiteleiting, Rule Basic Arceas Control, SMMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, R95 x 998 mm Shipping 24-in: 1293 x 695 x 998 mm 44-in: 1802 x 655 x 718 mm 44-in: 1802 x 655 x 718 mm Weight Printer 66-96 kg Printer 24-in: 1293 x 695 x 718 mm VHP Secure Boot, Whielex printhesds, introductory ink cartridge	Sheet size	
Thickness Up to 0.8 mm Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (virtual) ⁰ Mard disk 500 GB self-encrypting Connectivity Interfaces Bigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3u); Hi-Speed USB 2.0 certified interface for direct printing from USE flash drive Native print Languages Adobe PostScript 1.3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Windows, and macOS POF driver for Vindows B and above PDF driver for Windows and macOS PDF driver for Windows B and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPSec/Firewall, Certificates management, 802-1X, TLS 1.0/1.11.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (IDO S22.02.2-W), Secure File erase, self-encrypted HDD, PNI printing Dimensions (W x D x H) Printer Printer 24-in: 1293 x 695 x 998 mm Shipping 97-132 kg What's In the box HP Designlet Zhe SocScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapte ⁴ , quick reference guide, setup poster, power cord	Standard sheets	
Applications Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters Memory 128 GB (virtual) ^B Hard disk 500 GB self-encrypting Connectivity	Grammage	80 to 500 g/m²
Memory 128 GB (virtual) [®] Hard disk 500 GB self-encrypting Connectivity Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USE flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for mac/05, HP driver for Windows, HP SmartStream Drivers Raster and PostScript 1, Adobe PostScript Virtug support for Chrome OS, HP Print Service Plugin for Android, HP Smart Stream Drivers Raster and PostScript drivers for Windows and mac/OS PDF driver for Windows B and above Security features HP Secure Boot, Wintleisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0.1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Security features HP Secure Boot, Wintleisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.00.1.1/12, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Dimensions (W x D x H) Printer 24-in: 1293 x 695 x 998 mm Shipping Virtit 440.47, 666 x 718 mm <	Thickness	Up to 0.8 mm
Hard disk 500 GB self-encrypting Connectivity Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ub); Hi-Speed USB 2.0 certified interface for direct printing from USE flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for Turnor GS, HP driver for Undows, HP driver for Linux, printing support for Chrome GS, HP Print Service Plugin for Android, HP Smart Stream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows B and above PDF driver for Windows B and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.2-W), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D xH) Printer 24-in: 1293 x 695 x 998 mm 44-in: 1802 x 695 x 998 mm 44-in: 1802 x 695 x 998 mm 44-in: 1950 x 766 x 718 mm Weight Printer 66-96 kg Printer Printer 64-in: 128 y GU Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁶ , quick reference guide, setup poster, power cord HP Software and solution HP DesignLet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand an	Applications	Banners; Exhibition and event graphics; Light boxes - film; Maps; Orthophotos; Point of sale/display; Posters
Connectivity Interfaces Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USE flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS 64, HP-GL/2, HP-RTL Printing paths Apple AirPint, direct printing from USB flash drive, email printing, HP Click, HP driver for rulinox, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android HP SmartStream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows B and above Security features Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPV3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, IP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 24-in: 1293 x 695 x 998 mm 44-in: 1902 x 695 x 998 mm Shipping 24-in: 1293 x 695 x 998 mm Printer 66-96 kg Printer 66-96 kg Printer 100 kr reference guide, setup poster, power poster, power adapter ¹ , quick reference guide, setup poster, power b	Memory	128 GB (virtual) ⁸
Interfaces Gigabit Ethernet (1000Base-1) (802.3, 802.3u, 802.3ub); Hi-Speed USB 2.0 certified interface for direct printing from USE flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS 64, HP-GL/2, HP-RTL Printing paths Apple AliPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for marcOS, HP driver for Windows, AP driver for Unixx, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart 3pp for iOS and Android Drivers Raster and PostScript drivers for Windows and macOS POE driver for Windows B and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPV3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, IPW Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W X D x H) Printer Printer 66-96 kg Shipping 24-in: 1293 x 695 x 998 mm 44-in: 1802 x 695 x 998 mm 44-in: 1900 x 766 x 718 mm Weight Printer Printer 66-96 kg Shipping 97-132 kg What's In the box HP Designlet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adopter ⁴ , quick reference guide, setup poster, power cord Deperating temperature <td>Hard disk</td> <td>500 GB self-encrypting</td>	Hard disk	500 GB self-encrypting
Interfaces Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ub); Hi-Speed USB 2.0 certified interface for direct printing from USE flash drive Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS 6.4, HP-GL/2, HP-RTL Printing paths Appl AiPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Windows, AP driver for Unixx, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart 3pp for iOS and Android Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows Role Based Access Control, SNMPV3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/12, IP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer Printer 24-in: 1293 x 695 x 998 mm 44-in: 1802 x 695 x 998 mm 44-in: 1802 x 695 x 998 mm Meight Printer Printer 66-96 kg Shipping 97-132 kg What's In the box HP Design t26 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁴ , quick reference guide, setup poster, power cord HP Software and solutions HP Design t26 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁴ , quick reference guide, setup po	Connectivity	
Native print languages Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG, CALS G4, HP-GL/2, HP-RTL Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Vindows, HP SemartStream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates maragement, B02.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 24-in: 1293 x 695 x 998 mm Shipping 24-in: 1440 x 766 x 718 mm 44-in: 1950 x 766 x 718 mm 44-in: 1950 x 766 x 718 mm Weight Printer 66-96 kg Shipping 97-132 kg What's in the box HP Designet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁹ , quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges -25 to 55%C Acoustics -25 to 55%C Acoustics <t< td=""><td>Interfaces</td><td>Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive</td></t<>	Interfaces	Gigabit Ethernet (1000Base-T) (802.3, 802.3u, 802.3ab); Hi-Speed USB 2.0 certified interface for direct printing from USB flash drive
Printing paths Apple AirPrint, direct printing from USB flash drive, email printing, HP Click, HP driver for macOS, HP driver for Windows, HP Drint Service Plugin for Android, HP Smart app for iOS and Android HP SmartStream Drivers Raster and PostScript drivers for Windows and macOS PDF driver for Windows 8 and above Security features HP Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, Boz 1, 11/1, 1/1, 1/1 Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 24-in: 1293 x 695 x 998 mm Shipping 24-in: 1440 x 766 x 718 mm 44-in: 1950 x 766 x 718 mm Veight Printer 66-96 kg Sipping VH's in the box HP Designlet ZE PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁴ , quick reference guide, setup poster, power cord HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP Designlet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartTracker (optional) Derating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature 5 to 40°C	Native print languages	
PDF driver for Windows 8 and above Security features PDF driver for Windows 8 and above Security features PH Secure Boot, Whitelisting, Role Based Access Control, SNMPv3, HTTPS, Secure-IPP, IPSec/Firewall, Certificates management, 802 X17, VTS 1. 0/1. 1/1 2. PM Web Jetadmin compatible, PD JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 24-in: 1293 x 695 x 998 mm Shipping 24-in: 1440 x 766 x 718 mm 44-in: 1502 x 695 x 786 mm Weight Printer 66-96 kg Ge-96 kg What's in the box HP Design Jet Z6 PostScript Printer, printheads, Introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁴ , quick reference guide, setup poster, power cord HP Color Center, HP Partner Link, HP Design Jet Z6 PostScript Printer, printheads, Introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁴ , quick reference guide, setup poster, power cord Environmental ranges PO Click printing software, HP PrintOS, HP Web Jetadmin, HP Design Jet Utility including HP Color Center, HP Partner Link, HP JetAdvartage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Sto 40°C Operating temperature S to 40°C Operating humidity 20 to 80% RH Storage temperature S	Printing paths	HP driver for Linux, printing support for Chrome OS, HP Print Service Plugin for Android, HP Smart app for iOS and Android
Imagement, B0,21X, TLS 1,0/1.1/1 2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypted HDD, PIN printing Dimensions (W x D x H) Printer 24-in: 1293 x 695 x 998 mm 44-in: 1802 x 695 x 998 mm Shipping 24-in: 1400 x 766 x 718 mm 44-in: 1900 x 766 x 718 mm 44-in: 1900 x 766 x 718 mm 44-in: 1900 x 766 x 718 mm Weight Printer 66-96 kg Shipping 97-132 kg What's In the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁴ , quick reference guide, setup poster, power cord HP Software and solutions HP Dick printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP Detadvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges 5 to 40°C Operating temperature 5 to 55°C Acoustics 2-45 dB(A) (operating), 33 dB(A) (ide), <16 dB(A) (sleep)	Drivers	
Printer 24-in: 1293 × 695 × 998 mm Shipping 24-in: 1400 × 766 × 718 mm 44-in: 1950 × 766 × 718 mm Weight Printer 66-96 kg Shipping 97-132 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, Introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁴ , quick reference guide, setup poster, power cord HP Software and solution HP DesignJet Z6 PostScript Printer, printheads, Introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁴ , quick reference guide, setup poster, power cord HP Software and solutions HP DesignJet Z6 PostScript Printer, printheads, Introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁴ , quick reference guide, setup poster, power cord Environmental ranges HP Oick printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartTracker (optional) Operating temperature 5 to 40°C Operating temperature 5 to 50°C Acoustics Sound pressure Sound pressure 42-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	Security features	management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible,
44-in: 1802 x 695 x 998 mm Shipping 24-in: 1440 x 766 x 718 mm 44-in: 1902 x 766 x 718 mm Weight Printer 66-96 kg Shipping 97-132 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ³ , quick reference guide, setup poster, power cord HP Software and solutions HP Dick printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP Detadvartage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges 5 to 40°C Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics 2-45 dB(A) (operating), 33 dB(A) (ide), <16 dB(A) (sleep)	Dimensions (W x D x H)	
44-in: 1950 x 766 x 718 mm Weight Printer 66-96 kg Shipping 97-132 kg What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ⁹ , quick reference guide, setup poster, power cord HP Software and solution HP Dick printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges 5 to 40°C Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics 20 to 80% RH Sound pressure 42-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	Printer	
Printer 66-96 kg Shipping 97-132 kg What's in the box HP Design Jet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ² , quick reference quide, setup poster, power cord HP Software and solutions HP Cick printing software, HP PrintOS, HP Web Jetadmin, HP Design Jet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	Shipping	
Printer 66-96 kg Shipping 97-132 kg What's in the box HP Design Jet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core adapter ² , quick reference quide, setup poster, power cord HP Software and solutions HP Cick printing software, HP PrintOS, HP Web Jetadmin, HP Design Jet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	Weight	
Shipping 97-132 kg What's in the box HP Design.let Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3- in core adapter ² , quick reference guide, setup poster, power cord HP Software and solutions HP Cick printing software, HP PrintOS, HP Web Jetadmin, HP Design.let Utility including HP Color Center, HP Partner Link, HP DetAdvantage Security Manager (optional), HP SmartTracker (optional), HP SmartTracker (optional) Environmental ranges Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics 42-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	-	66-96 kg
What's in the box HP DesignJet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3- in core adapter ³ , quick reference guide, setup poster, power cord HP Software and solutions HP Lick printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP DetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges 5 to 40°C Operating temperature 5 to 50°C Acoustics 20 to 80% RH Storage temperature -25 to 55°C Acoustics 2-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)		
HP Software and solutions HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link, HP JetAdvantage Security Manager (optional), HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 42-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)		HP Design Jet Z6 PostScript Printer, printheads, introductory ink cartridges, printer stand and media bin, spindle, 3-in core
Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics	HP Software and solutions	HP Click printing software, HP PrintOS, HP Web Jetadmin, HP DesignJet Utility including HP Color Center, HP Partner Link,
Operating humidity 20 to 80% RH Storage temperature -25 to 55% C Acoustics 22-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep) Sound pressure 42-45 dB(A) (operating), 5.1 B(A) (idle), <3.4 B(A) (sleep)	Environmental ranges	
Operating humidity 20 to 80% RH Storage temperature -25 to 55% Acoustics	Operating temperature	5 to 40°C
Storage temperature -25 to 55% Acoustics Sound pressure 42-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)	Operating humidity	20 to 80% RH
Sound pressure 42-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)		-25 to 55%C
Sound pressure 42-45 dB(A) (operating), 33 dB(A) (idle), <16 dB(A) (sleep)		
Sound power 6.0-6.3 B(A) (operating); 5.1 B(A) (idle), <3.4 B(A) (sleep)		42-45 dB(A) (operating), 33 dB(A) (idle), <16 dR(A) (sleen)
Power Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)		
Consumption <100 W (printing); <32 W (ready); <6.5 W (sleep); 0.1 W (off)		איז ביר אוויסטוויסט אין איז
		<100 W (printing): <22 W (randu): <6 5 W (rloop): 0.1 W (off)

Certification

Safety	USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Singapore (PSB); China (CCC); Argentina (IRAM); India (BIS)
Electromagnetic	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC), South Africa (SABS)
Environmental	ENERGY STAR; ErP; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT
Warranty	One-year limited hardware warranty

Ordering information

Product	-	
T8W15A T8W16A	HP Design Jet Z6 24-in PostScript Printer	
T8W18A	HP Design Jet Z6 44-in PostScript Printer HP Design Jet Z6dr 44-in PostScript Printer with V-Trimmer	
	The besigned 20di 44 introdescript finiter with V finitiner	
Accessories		
1QF38A	HP DesignJet 44-in Take-up Reel	
5EK00A	HP HD Pro 2 42-in Scanner	
5EK01A	HP SD Pro 2 44-in Scanner	
8SW00A 8SW00AAE	HP SmartStream USB Preflight Manager HP SmartStream Preflight Manager	
8SW01A	HP SmartStream Print Controller USB for HP DesignJet Printers	
8SW01AAE	HP SmartStream Print Controller for HP DesignJet Printers	
8SW11A	HP SmartTracker USB for DesignJet	
8SW11AAE	HP SmartTracker for DesignJet	
CN538A	HP DesignJet 3-in Core Adapter	
CQ783A Q6709A	HP DesignJet 24-in Spindle HP DesignJet 44-in Spindle	
Original HP printing		
3WX35A	HP 746B 300-ml Photo Black DesignJet Ink Cartridge	
3WX36A	HP 746B 300-ml Cyan DesignJet Ink Cartridge	
3WX37A 3WX38A	HP 746B 300-ml Magenta DesignJet Ink Cartridge HP 746B 300-ml Yellow DesignJet Ink Cartridge	
P2V25A	HP 746 DesignJet Printhead	
P2V81A	HP 746 300-ml Chromatic Red DesignJet Ink Cartridge	
P2V83A	HP 746 300-ml Matte Black Design Jet Ink Cartridge	
Use Original HP ink	s and printheads, and HP large format printing materials, to experience consistent	
	iable performance that enable less downtime. These critical components are	
	neered together as an optimized printing system, and Original HP inks are designed	
	e of HP printheads. Protect your HP printer investment by using Original HP inks for	
	otection. For more information, visit hp.com/go/OriginalHPinks.	
Original HP large fo	ormat printing materials	
Q6581A HP Univers	sal Instant-dry Satin Photo Paper (FSC® certified) ¹⁰ (Recyclable) ¹¹ 1067 mm x 30.5 m	
(42 in x 100 ft)		
	atte Canvas 1118 mm x 15.2 m (44 in x 50 ft)	
<pre>cb5b9c HP Heavyv ft)</pre>	veight Coated Paper (FSC® certified) ¹⁰ (Recyclable) ¹¹ 1067 mm x 30.5 m (42 in x 100	
	ay Matte Polypropylene, 2 Pack (Recyclable) ¹¹ 1067 mm x 30.5 m (42 in x 100 ft)	
CG460B HP Premiu	im Matte Photo Paper (FSC® certified) ¹⁰ (Recyclable) ¹¹ 914 mm x 30.5 m (36 in x 100	
ft)		
For the entire HP Li	arge Format Printing Materials portfolio, please see HPLFMedia.com.	
Service and Suppor	t	
117VPQE UD Installa	tion Service Moderate Level	
	Next Business Day with Defective Media Retention Support for HP DesignJet Z6 24in	
U9YZ1E HP 3 year Next Business Day with Defective Media Retention Support for HP DesignJet Z6 44in		
U9ZE2E HP 3 year Next Business Day with Defective Media Retention Support for HP DesignJet Z6dr		
44in		
	Next Business Day with Defective Media Retention Support for HP DesignJet Z6 24in	
U9YZ3E HP 5 year Next Business Day with Defective Media Retention Support for HP DesignJet Z6 44in		
44in	Next Business Day with Defective Media Retention Support for HP DesignJet Z6dr	
	r Post Warranty, Next Business Day with Defective Media Retention Support for HP	
DesignJet Z6 24in		
	r Post Warranty, Next Business Day with Defective Media Retention Support for HP	
DesignJet Z6 44in	r Post Warranty, Next Business Day with Defective Media Retention Support for HP	
DesignJet Z6dr 44i		
-	 is offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more	
information, please	e visit http://www.hp.com/go/cpc	
¹ Maximum rate of	output for color image 100% color coverage. Printed on maximum roll size, with	
Original HP Vivid Photo Inks.		
² Mechanical printing time with Original HP Vivid Photo Inks. Measured on a 44-in printer.		
³ Borderless printing available on photo gloss, photo satin, polypropylene, and backlit roll media.		
* Except self-adhesive vinyls and non-cuttable medias.		
number, on AU/E1	cified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative	
⁶ Measured on HD I	cified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative IP Matte Film in Best or Normal mode with HP Vivid Photo Inks.	
⁶ Measured on HP I	cified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative iP Matte Film in Best or Normal mode with HP Vivid Photo Inks. Matte Film.	
 ⁶ Measured on HP I ⁷ With HP Premium ⁸ Based on 4 GB RA 	cified vector length or ±0.2 mm (whichever greater) at 25°C (73°F), 50-60% relative PM Patte Film in Best or Normal mode with HP Vivid Photo Inks. Matte Film. Instant-dry Satin Photo Paper with HP Vivid Photo Inks. M.	
 ⁶ Measured on HP I ⁷ With HP Premium ⁸ Based on 4 GB RA ⁹ Not included in th 	cified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative 4P Matte Film in Best or Normal mode with HP Vivid Photo Inks. Matte Film. Instant-dry Satin Photo Paper with HP Vivid Photo Inks. M. e box for 24-in models.	
 ⁶ Measured on HP I ⁷ With HP Premium ⁸ Based on 4 GB RA ⁹ Not included in th ¹⁰ BMG trademark 	cified vector length or ±0.2 mm (whichever greater) at 25°C (73°F), 50-60% relative PM Patte Film in Best or Normal mode with HP Vivid Photo Inks. Matte Film. Instant-dry Satin Photo Paper with HP Vivid Photo Inks. M.	

¹⁴ Brid valuelinal knows (2000) and (20







Mac Windows 10



