

# CONVEYOR BELT

## CB 3000 / 5000 / 8000

The ASCO® CB 3000 / 5000 / 8000 conveyor belt is a robust and powerful conveying system, ideally suited for a wide range of transport applications across various industries. Thanks to its solid construction and high-quality components, it has been specifically designed for long-term use under demanding conditions.

### △ HIGHLIGHTS

- Operating hourcounter
- Easy belt and angle adjustment
- Length extension

**CB 3000**



### △ TECHNICAL DATA

- △ Speed: up to 210 cm/s
- △ Capacity: up to 120 m<sup>3</sup>/h
- △ Belt width: 0,6 m
- △ Hopper length: 0,8 - 1,6 m
- △ Hopper capacity: 0,2 or 0,5 m<sup>3</sup>
- △ Drive power: 400 V / 2,2 kW
- △ Weight: 565 kg
- △ Width: 1,3 m
- △ Length: 3,4 m
- △ Height: 0,82 m
- △ Recommended amperage for fuses: 16 A

**CB 5000**



### △ TECHNICAL DATA

- △ Speed: up to 210 cm/s
- △ Capacity: up to 110 m<sup>3</sup>/h
- △ Belt width: 0,6 m
- △ Hopper length: 0,8 - 1,6 m
- △ Hopper capacity: 0,2 or 0,5 m<sup>3</sup>
- △ Drive power: 400 V / 2,2 kW
- △ Weight: 760 kg
- △ Width: 1,2 m
- △ Length: 5 m
- △ Height: 0,82 m
- △ Recommended amperage for fuses: 16 A

**CB 8000**



### △ TECHNICAL DATA

- △ Speed: up to 210 cm/s
- △ Capacity: up to 100 m<sup>3</sup>/h
- △ Belt width: 0,6 m
- △ Hopper length: 0,8 - 1,6 m
- △ Hopper capacity: 0,2 or 0,5 m<sup>3</sup>
- △ Drive power: 400 V / 2,2 kW
- △ Weight: 1060 kg
- △ Width: 1,2 m
- △ Length: 8 m
- △ Height: 0,82 m
- △ Recommended amperage for fuses: 16 A

**NOTE:** If connection to a supply protected by an RCD is required, a suitable RCD type B or equivalent protective measure shall be provided by the customer.

