


## DIESEL ENGINE DRIVEN GENERATING SET 1500 r.p.m.

**STAGE 5  
CERTIFIED**



YANMAR



1500  
RPM



LWA  
2000/14/CE

NOISE  
level



WATER  
cooled



DIESEL



THREE  
phase



### MGTP 32 YR

Code **RP352-32TS0**

### TECHNICAL DATA

PRP Prime Power	kVA	32
LTP Limited Time Power	kVA	35
Prime Power (cos φ = 0,8)	kW	25,6
Limited Time P. (cos φ = 0,8)	kW	28
Three-phase Voltage	V	400
Single-phase Voltage	V	230
Power factor (cos φ)		0,8
Frequency	Hz	50
RPM		1500

### GENERATOR

LINZ / MECC ALTE / STAMFORD

Insulation Class	H
Mechanical protection	IP23

### ENGINE

Type	YANMAR 4TNV98C-IYE
EU Emission Stage	Stage V
N° cylinders	3
Displacement	cm <sup>3</sup> 1861
Speed regulation	Electrical
Cooling	Water
Fuel	Diesel

### Fuel Consumption

Fuel Tank capacity	lt.	185
Fuel consumption 75% load PRP	l/h	6,9
Running time	h	27

### NOISE LEVEL

Noise level	Lwa	90
Acoustic pressure level 7m	dBA	65

### DIMENSIONS & WEIGHT

Dry weight	Kg	1050
Dimensions (L. x W. x H.)	mm	2300 x 1130 x 1580

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.

### DISTRIBUTION PANEL:

4 x 16A 230V with ELCB  
1 x 32A 400 V with ELCB

### STANDARD FEATURES:

Built in fuel tank  
Bunded tank  
12V Battery  
Battery switch  
Forklift pocket  
Central lifting eye  
Exhaust gas silencer  
Soundproof canopy  
3 ways valve for external fuel tank connection

### ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 7310  
ON/OFF switch  
Safety cover for DSE 7310 and ON/OFF switch  
Main circuit breaker  
Earth leakage relay  
Remote start/stop connector  
Emergency stop

### OPTIONS



Site tow trailer



Road tow trailer