



ES0607DC

Paved surface scissor lift

LIST OF STANDARD EQUIPMENT

- Automatic pothole protection system
- Crushing protection
- High ground clearance
- Self-locking door on the platform
- Speed limit at maximum height
- Platform load sense system
- Automatic braking system
- Emergency brake release
- Non-marking tyres
- Tilt indicator with alarm
- Warning siren during lowering and dual flashing LED light
- Safety bracket for maintenance operations
- Horn
- Cylinder locking valve
- Emergency stop button
- Emergency lowering
- Traction engine protection
- Anchoring eyebolts
- Onboard diagnostics system
- Hour counter
- Proportional controls
- Fold-down guardrails
- Power to platform
- Maintenance free battery
- Explosion-proof tubing system
- Motion Alarm
- Integrated holes for fork transport
- Charging protection system
- Charging indicator
- Tie-down and lifting points
- One way platform extension deck
- Two-wheel drive
- Two-wheel steering
- Manual emergency brake release



LOGISTICS



CONSTRUCTION

ES0607DC

Load capacity	240 kg
Load capacity when extended	100 kg
Max no. Occupants (Indoor/outdoor)	2/1
Working height	A 5.6 m
Platform floor level height	B 3.6 m
Overall length	C 1.44 m
Overall width	D 0.76 m
Overall height (rails up)	E 1.99 m
Transport height (rails down)	F 1.62 m
Platform dimensions (length/width)	1.29x0.7 m
Platform extension	G 0.6 m
Ground clearance (stowed)	6 cm
Ground clearance (raised)	1.5 cm
Wheelbase	H 1.05 m
Turning radius (inside)	40 cm
Turning radius (outside)	1.55 m
Driving motors	2x24VDC/0.4kW
Lifting motors	24VDC/1.2kW
Travel speed (stowed)	4 km/h
Travel speed (raised)	0,6 km/h
Batteries	24 V/85 Ah AGM batteries maintenance free
Integrated battery charger	24V/15A
Gradeability	25%
Maximum working slope	1,5°/3°
Non-marking tyres	230x80 mm
Weight (CE)	920 kg

STANDARDS MET: EN 280-1, ANSI/SAIA A92.20

The data given in this brochure are provided for information purposes and are subject to change without prior notice.
All images are purely guideline and might not give an exact representation of the product.



Non-marking solid tyres



Safety bracket

