

## Technische Daten/Abmaße

MODELL	RL1250	RL2000	RL3000	RL4500	RL6500	RL8500	RL11000
TRAGFÄHIGKEIT (KG)	1250	2000	3000	4500	6500	8500	11000
GEWICHT (KG)	757	930	1477	3012	3424	4360	5100
MAXIMALER BETRIEBSDRUCK (BAR)	100	100	100	100	100	100	100
MAXIMALES DREHMOMENT IN NM	490	1250	1960	5300	7650	8100	10790
A	Min. 540	Min. 550	Min. 740	Min. 830	Min. 900	Min. 980	Min.1100
	Max. 1120	Max.1300	Max.1620	Max.2085	Max. 2380	Max.2740	Max.2900
B	Min. 700	Min. 720	Min. 720	Min. 860	Min. 960	Min. 1180	Min. 1300
	Max. 1280	Max. 1400	Max. 1570	Max. 2120	Max. 2420	Max. 2940	Max. 3150
C	1900	2400	2400	3000	3600	3900	4900
D	1760	1660	1825	2270	2300	2480	2480
E	750	930	930	1250	1400	1500	1500
F	Ø800	1100x1100	1100x1100	1500x1500	1500x1500	1800x1800	1800x1800
HYDRAULISCHER MOTOR (KW)	2,2	2,2	4	5,5	5,5	7,5	9

