

SKAKO DARTEK

TECHNICAL DATAS

Product characteristics:

- Production: MOR
- Gran size: 0 - 80 mm
- Density: 0,4 - 0,5Tn/m³
- Temperature: Ambient
- Humidity: 55 %

Production characteristics:

- Capacity: 50 Tn/h
- Screening size: 10 - 15 mm
- Machine production: Continuous.
- Material behaviour: Known



SKAKO DARTTEK

VIBRATING FLIP-FLOP SCREEN MODEL “ZXX 2400/7200”

- **Machine Characteristics:**

- Working length: 7200 mm
- Working width: 2400 mm
- Working surface: 17,30 m²
- Frame: Carbon steel
- Execution: Supported
- Slope: 20°
- Number of decks: 1
- Screen surface: Elastic polyurethane panels
- Screening opening: 1-15 mm
- Maths side closure: Polyurethane wedges
- Cover: Included, rubber
- Vibrating weight: 7.500 kg

- **Vibrator characteristics:**

- Type of vibrator: 2 Mechanical Vibrators
- Centrifugal force: 42.500 kg
- Frequency: 860 r.p.m.
- Motor:
 - Supply: Triphase 400 V, 50 Hz
 - Power: 24 Kw
 - Speed: 860 r.p.m.

- **Vibration characteristics:**

- Stroke: 8 mm
- Frequency: 950 r.p.m.
- Aceleration: 4,6 G
- Stroke subresonant frame: 8 mm + 8 mm = 16 mm

- **Suspension system:**

- Tipo de antivibrantes: 8 AMC suspensions model AB-HD-50-2
- Isolation: 90%
- Dynamic load: 4200 daN
- Frequency: 20 Hz

- **Paint finishing:**

- Cleaning and degreasing of surfaces.
- Primary coat: glycerophtalic, 70 μ.
- Finishing coat: glycerophtalic, 40 μ.
- Color RAL to be defined