



EASY POWER E



Il mix perfetto tra compattezza e prestazioni
 The perfect mix between compactness and performances

SETTORI DI UTILIZZO



SECTOR OF USE



Comet TW Premium



Comet TW 500
Premium



- Motori asincroni trifase 15-22 kW Nicolini, dotati di giunto elastico.
- Pannello di controllo con avviamento stella-triangolo e comandi in bassa tensione (24 V).
- Robusto telaio tubolare verniciato con trattamento anticorrosione.
- Impugnature ergonomiche per agevolarne la manovrabilità.
- Pannelli di rivestimento in acciaio inox AISI 304.
- Pratici alloggiamenti per pistola e lancia.
- 4 ruote schiumate Ø 320 "all-road" con cuscinetti a rulli.
- Quadro comandi con interruttore generale, pulsanti di accensione e spegnimento, stop di emergenza, contatore, teleruttore con relè termico per la protezione del motore.
- Aspirazione acqua diretta, pompe autoadescanti.
- Manometro DN 63 in acciaio inox con glicerina.
- Valvola unloader in acciaio inox a rilascio di pressione (ripristino al 50% della pressione impostata) ed EASY START.
- Filtro acqua 100 mesh con cartuccia facilmente sostituibile.

- Asynchronous three-phase motors 15-22 kW Nicolini, with flexible motor-pump coupling joint.
- Industrial low voltage (24 V) control panel with star-delta starter.
- Sturdy painted tubular frame with anti-corrosion treatment.
- Ergonomic grips for easy maneuverability.
- AISI 304 stainless steel coated panels.
- Practical housing for gun and lance.
- Ø 320 "all-road" foamed wheels with roller bearings.
- Control panel with main switch, on/off buttons, emergency stop, hour counter, contactor with thermic relay for motor protection.
- Direct water suction, self priming pumps.
- S/S DN 63 pressure gauge with glycerin.
- Stainless steel Unloader valve with pressure release system (reset at 50% of set pressure) and EASY START system.
- 100 mesh water filter with easily replaceable cartridge.

Modello Model	Pompa Pump	RPM			A	Ph-V-Hz	l/min	bar	HP	kW	kg	(L x W x H) cm
EASY POWER E 30/300	Comet TW	1450	32	3-400-50 3-440-60	30 15 21	300 500 500	30,0 20,0 25,0	22,5 15,0 18,5	185 175 195	100 x 75 x 95		
EASY POWER E 15/500			63									
EASY POWER E 21/500			63									

Disponibile anche in versioni ATEX - EX / Also available in ATEX - EX version

