



KRM 10/4.0 shown including optional equipment (motorized rear roll adjustment)



See this machine in action on YouTube 

- Hardened rollers, suitable for stainless steel
- Motor driven left/right direction, operated with foot switch
- Hand wheel for rear roll feed
- Quick adjusting rolls (motor-driven, option)
- Standard series wire core groove
- Top roll swings out across cam lock
- Supplied with conical bending feature

Specifications KRM

		10/4,0	10/5,0	12/4,0	12/5,0	15/3,0	20/4,0
Working length	mm	1.050	1.050	1.250	1.250	1.550	2.050
Plate thickness (max.)	mm	5	5,5	4,5	5,5	3,5	4,5
Max. plate thickness for bending	mm	4	5	4	5	3	4
Bending diameter (min.)	mm	150	190	175	210	150	210
Roll diameter	mm	110	130	120	140	110	140
Motor rating main drive	kW	2,2	2,2	2,2	2,2	2,2	2,2
Overall dimensions (length x width x height)	m	1,82x0,85	1,82x0,9	2,02x0,85	2,02x0,9	2,62x0,85	3,24x0,9
Weight	kg	1.080	1.220	1.250	1.365	1.220	1.530
Part No.		131960	131961	131963	131964	131965	131968



Standard Equipment

hardened rollers, conical bending feature