

PRODUCT SAFETY DATA SHEET



Océ-Technologies B.V.

St. Urbanusweg 43
P.O. Box 101
5900 MA Venlo
The Netherlands

telephone +31 77 359 2222

A CANON COMPANY

Number: EN-HYB340-360-b-HQ

Date: November 2018

For safety questions contact the Product Safety Coordinator of your local sales and service organisation

Product Name(s)	Océ Arizona® 1240 GT, Océ Arizona® 1260 GT, Océ Arizona® 1280 GT, Océ Arizona® 1240 XT, Océ Arizona® 1260 XT, Océ Arizona® 1280 XT all with option RMO	
Model(s)	HYB340 and HYB360	
Description Process speed	Flatbed digital color print system Océ Arizona 12x0 GT up to 33,6 m²/h and Océ Arizona® 12x0 XT up to 35,0 m²/h Option RMO - Roll Media Printing Up to 25,6 m²/h	
Dimensions: * width * depth * height * weight	Océ Arizona® 12x0 GT 4656 mm 2000 mm (2285 mm with RMO) Table 888 mm and Gantry 1300 mm 785 kg, with RMO 960 kg	Océ Arizona® 12x0 XT 4556 mm 3830 mm (4120 mm with RMO) Table 888 mm and Gantry 1300 mm 1625 kg, with RMO 1800 kg
Electrical data: * voltage * current-rated * building fuse Mains connection Safety class Protection class EMC Class Safety certification Battery Type (weight)	Océ Arizona® 12x0 GT 200 – 240 V 50/60Hz 8 A Inlet 1 and 8 A Inlet 2 20 A USA and 16 A EU Cable with plug I (IEC 61140) Protective earth connection IPX0 (IEC 60529) Class A (according to EN61000-6-4) According to 2006/42/EC BG-listed (DP 18067), UL73 and CSA 22.2 No. 68 CR2032 (3,3 grams, present on CPU)	Océ Arizona® 12x0 XT 10 A Inlet 1 and 8 A Inlet 2
Energy consumption: * off * ready * maximum	Océ Arizona® 12x0 GT 0 W 200 W 1500 W Inlet 1 and Inlet 2	Océ Arizona® 12x0 XT 0 W 200 W 1500 W Inlet 1 and 1900 W Inlet 2
Noise emission¹: * Sound pressure level (at operator position) Heat emission Radio interference Radiation Chemical emission: * dust * ozone * TVOC	L _{pA} less than 71 dB (A) Not applicable Complies with Directive 2004/108/EC and FCC rules and regulations, part 15 Class A. Not applicable Emission (mg/h) Concentration (mg/m³) ¹ 6,8 0,006 31,2 0,016 47,6 0,10	
Recommended room ventilation	≥ 1200 m³ per hour. For heat evacuation extra ventilation may be necessary.	
Consumables	This apparatus is suitable for IJC255, IJC256, IJC257 and IJC258 Ink Materials	
Additional safety information	UV inks can be harmful if not properly handled. Follow the guidelines in the User Guide carefully in order to ensure maximum safety.	

¹ average concentration, additional to background, calculated for a daily volume of continuous prints during a work time of 8 h at recommended minimal room volume and room ventilation. Under normal conditions of use concentrations are considered to remain around or below above concentrations. Concentrations are a best estimate and have been calculated from concentration measurements performed under practical conditions in a room with a volume of 195 m³ and a ventilation rate of 6/h.

CE-Compliance



Approval according to Machinery Directive 2006/42/EC



Approval according to standard UL73 and CSA 22.2 No. 68



Approved according to 2014/30/EU ²

²Report available on request.

This safety data sheet has been compiled to the best of our knowledge as a compact guide to safe handling of this product. We reserve the right to revise safety data sheets as new information becomes available. It is the user's responsibility to determine the suitability of this information for the adoption of safety precautions as may be necessary and to contact the company to make sure that this sheet is the latest one issued. If and in so far as limitation of liability is permitted under the applicable laws, we do not accept liability for any inaccuracy that may occur in this information.