



Tomás Guillén

MAQUINARIA PARA LA INDUSTRIA ALIMENTARIA



STERIFLOW BARRIQUAND S/S STATIC AUTOCLAVE 6 B



ID:	0000000202734
MAKE	BARRIQUAND STERIFLOW
VOLUME	11750 L
WORKING PRESSURE	5 BAR
NUMBER OF BASKETS	6
TEST PRESSURE	150°C
TEST PRESSURE	5 BAR
PRESSURE TEST	8.6 BAR
INCLUDED	TUBULAR HEAT EXCHANGER
SYSTEM	DE CASCADA
CATEGORY	B
INCLUDED	DOUBLE DOOR
CONTROL PANNEL	INCLUDED
MADE OF	STAINLESS STEEL
MODEL	STERIFLOW 1462 EL
No. DOORS	2
POWER	13 KW / 17.70 HP



STERIFLOW BARRIQUAND S/S STATIC AUTOCLAVE 6 B

SPACE TOTAL DIMENSIONS			
LENGTH	7,720 m	WIDTH	2,462 m
HEIGHT			
HEIGHT	3,175 m	WEIGHT	4.000,00 Kg

WORKING DIMENSIONS			
LENGTH	6,884 m	WIDTH	1,450 m
HEIGHT	0,000 m		

DESCRIPTION

Autoclaves are used for the sterilization of packaged products that need to reach high temperatures (+100°C) for the elimination or inactivation of pathogenic microorganisms.

Static autoclaves: these are suitable for any format and are used for food packaged in cans, jars and other flexible materials.

Inner diameter: 1,450 m.

Characteristics:

STEAM CONSUMPTION:

- Steam consumption (6 Bar): 630 kg.
- Flow rate: 2.000 kg/h.

COLD WATER CONSUMPTION:

- Consumption (4 Bar) : 12 m³
- Flow rate: 40 m³/h.

COMPRESSED AIR CONSUMPTION:

- Consumption (6 Bar): 16 Nm³
- Flow rate: 160 Nm³/h.

TUBULAR HEAT EXCHANGER:

- Make: STERIFLOW
- Model: HEAT EXCHANGER IJMS
- Capacity: 170 L.
- Surface area: 17 m²

