

2.2 TAP-HD Series Technical Specifications

TAP-HD Model**

MODEL	TAP-3-HD
CAPACITY (LOADING)	3MT @ 165mm
CAPACITY (TILTING)	3MT @ 165mm
ROTATING SPEED (RPM)	0.061 to 0.61 RPM
TILT RANGE OF TABLE	0-135 °
TILT RANGE OF ARM	0-45 °
INCOMING SUPPLY	380/400/415V-3P-50Hz 440/460/480V-3P-60Hz
FUSES	9 Amp
CONTROL VOLTAGE	24VAC
DIAMETER OF TABLE	ø1000
IP CLASSIFICATION	IP 54
EARTHING	800 Amp
MAX. TILTING HEIGHT (H)	1738
WEIGHT (KG)	1935
DIMENSIONS (LxHxW)	1280x1058x2280

* Technical Specification as accurate from (Latest GA Drawing).

2.3 Machine Plate

Machine plate is attached to the control cabinet.

 ROMAR POSITIONING EQUIPMENT INTERNATIONAL PTE LTD 38 JOO KOON CIRCLE, JURONG SINGAPORE 629063 E-MAIL: after-sales@romar.com.sg AN ESAB GLOBAL COMPANY	
PRODUCT NAME:	
MODEL:	
PART NO :	
CAPACITY:	
SERIAL NO :	
MFG. DATE:	
VOLTAGE/AMPERE/HZ/IP:	
WEIGHT:	
MADE IN CHINA	CE

It has important information:

Product Name	Equipment Name
Model	The type of machine
Part.No.	The ESAB article number for the machine
Capacity	The capacity of machine
Serial No.	The serial number of machine
MFG Date	The manufacturing year of the machine.
Voltage/Ampere/HZ/IP	Voltage Supply Requirement
Weight	The weight of the machine.

NOTE! THE WEIGHT IS WITHOUT ACCESSORIES!

The machine plate has electrical information:

Hz	Mains supply connection Hz
V	Mains supply connection V
KW	Mains supply connection KW

NOTE! WHEN ORDERING SPARE PARTS, PLEASE STATE ALL THE INFORMATION IN MACHINE PLATE!