

TSH Twinstacker with SPA Twin lateral pack output

	TSH SPA Twin 50	TSH SPA Twin 70	TSH SPA Twin 100
MCT control system			
Max. sheet size, width × length cm (in)	50 × 34 /47.5 × 31.5 ¹ (19.69 × 13.39/ 18.70 × 12.40 ¹)	70 × 34 /67.5 × 31.5 ¹ (27.56 × 13.39/ 26.57 × 12.40 ¹)	100 × 34/97.5 × 31.5 ¹ (39.37 × 13.39/ 38.39 × 12.40 ¹)
Min. sheet size, width × length cm (in)	10 × 10 (3.94 × 3.94)	10 × 10 (3.94 × 3.94)	10 × 10 (3.94 × 3.94)
Max. product thickness mm (in)	6 (0.24)	6 (0.24)	6 (0.24)
Max. pile height per level cm (in)	10 (3.94)	10 (3.94)	10 (3.94)
Max. multiple-ups	2	3	4 (3 ¹)
Repeat width with 2 repeats max. mm (in)	240/212 ¹ (9.45/8.35 ¹)	340/312 ¹ (13.38/12.28 ¹)	490/462 ¹ (12.29/18.19 ¹)
Repeat width with 3 repeats max. mm (in)		215/192 ¹ (8.46/7.56 ¹)	316/292 ¹ (12.44/11.50 ¹)
Repeat width with 4 repeats max. mm (in)			230/207 ¹ (9.06/8.15 ¹)
Maximum speed (sheets/h)	18,000 ¹	18,000 ¹	18,000 ¹
Removal height cm (in)	Level 1: 81.5 (32.09) Level 2: 107.5 (42.32)	Level 1: 81.5 (32.09) Level 2: 107.5 (42.32)	Level 1: 81.5 (32.09) Level 2: 107.5 (42.32)
Length of buffer section on each level m (in)	1.55 (61.02)	1.55 (61.02)	1.55 (61.02)
Power consumption kVA 3 × 400 V, 50/60 Hz 3 × 230 V, 50/60 Hz	3.9 3.9	3.9 3.9	3.9 3.9
Compressed air supply	6 bar, 400 NL (dry, filtered air provided by customer)		

¹ With automatic jogging device