



A reliable partner that gets the job done - the SuperCombi from Rolba!

The SuperCombi is built to make your work easier and more efficient. With its large tank volume and efficient functions, it is perfect for anyone looking for a reliable unit that can handle demanding, high capacity tasks.

Designed for durability

Ergonomic hose handling and a robust, stainless steel construction ensure a long service life and reliable operation. The hydraulically opening rear hatch together with the tank's tipping function facilitates unloading and cleaning. Thanks to carefully selected pumps and cabinets made of the highest quality materials, the machine requires minimal maintenance year after year.

Adapted for harsh environments

The SuperCombi can be adapted to operate efficiently in temperatures down to -25 degrees. With a robust, stainless steel tank, the machine withstands even the harshest of environments. Work lights and warning lights ensure full visibility at all times, and an additional outer flap protects the jetting hoses from the elements. This means that you can rely on your SuperCombi in all environments and climates.

User Friendly technology

With our easy-to-understand displays, you can easily keep track of engine speed, water and sludge levels in the tank, and monitor fuel consumption in real time. You can also adjust the jetting pressure, measure the hose length with precision, automatically stop the jetting hose feed and determine the value at which the vacuum pump should turn off, making every task easier and more efficient.

Innovative Features

- Unique tank design in stainless steel provides even weight distribution over the axles as well as a high load capacity.
- Ergonomic jetting equipment and crane arm that makes work easier for the operator.
- Flexible and easy-to-use control system that optimises fuel savings.
- Oil-free air compressor as standard – unique to Rolba and a guarantee of maximum performance with minimal environmental footprint. The oil-free technology also ensures that you avoid oil mist during use.
- The water pump is powered directly from the chassis PTO to reduce energy loss and improve efficiency.



SuperCombi

Description	
Tank	14–18 m³, stainless. Tipping function.
Vacuum pump	33,000–38,000 l/min.
Jetting pump	340, 412 l/min 170 bar. 390, 480 l/min 150 bar.
Drainage pump	1,500 l/min.
Crane and crane hose	15–18 m 4", 5" suction hose.
Suction hose reel	1–2 units, 30 m on each, 3" hose.
Jetting hose	½", 80 m–120 m. 1", 120 m–180 m hose spreader.
Cabinet, storage	Stainless steel cabinet, LED light, insulated.
Remote control	Joystick operated transmitter with display and a handheld transmitter.

Options (examples)	
Classification	ADR.
Jetting hose	1 ¼" as option.
Hot water boiler	
Extra jetting pump	400 bar, 37 l/min.
Tank jetting	
VacGuard	Reduces fuel consumption.
Central locking for cabinet	
Heated cabinets	
Working light LED bar	Mounted along the side.



The product(s) in the images may be equipped with optional features.