

## EDGER/MULTIRIP SAW, MODEL KME2-750R YEAR 2012



## TECHINICAL SPECS

### NOT DRIVEN 4 M INFEED TABLE

#### 1 EDGER/MULTIRIP SAW, MODEL KME2-750R

- Opening width: 750 mm
- Max. cutting height: 125 mm
- Min. workpiece length: 800 mm
- Max. saw blade dia.: 380 mm
- Saw shaft diameter: 60 mm
- Speed of saw shaft: 3300 rpm
- Hydr. feed drive 3 - 85 m/min,

Infinitely variable, driven from the saw shaft, consisting of variable pump and hydraulic motor

Bottom saw shaft rotating against the feed, hard-chrome plated

- 5 powered feed rollers
- Motor mounting device, 22 kW
- Anti-kickback device,

1 MOTOR 22KW 400V/50HZ  
incl. V-belt drive  
motor mounting version **C**

1 ROLLER PRESSURE AMPLIFIER (SET)  
for KME2/BM, adjustable, spring-loaded

BASIC HYDRAULIC EQUIPMENT  
required for the hydraulic feed

1 MECH. TOP ROLLER ADJUSTMENT  
by a hand wheel, for KME2/BM

#### ELECTRICS

1 BASIC ELECTRICS

- emergency stop circuit
- safety switch
- standstill monitoring
- wiring/cabling

**PRODUCER: PAUL MASCHINENFABRIK GERMANY**

### NOT DRIVEN 4 M OUTFEED TABLE

**PRICE excl. VAT ..... 14.000 eur**





**Florin Iancu**

C.E.O.

mobil +40 726 700 990

[florin.iancu@woodexpert.ro](mailto:florin.iancu@woodexpert.ro)

040431 Bucharest, sector 4, str. Albinelor, nr. 7, et. 1

[www.woodexpert.ro](http://www.woodexpert.ro)