

Developed for professional use in industry, the H-Series is available in a wide range of pressure and flow combinations up to 500 bar and 60 L/min. This allows exact adaption to any customer requirement. These machines are designed for continuous use in demanding cleaning tasks, when there must be no compromises.

**INCLUDED****Standard accessory kit SWS up to 350 bar:**

- 10 m high-pressure hose DN10, kink protection on both sides
- HDP350 high-pressure gun with quick coupling and swivel joint in the inlet
- Double jet pipe made of stainless steel with high- and low-pressure nozzle

**Standard accessory kit from 400 bar:**

- 10 m high-pressure hose DN10, kink protection on both sides
- High-pressure gun HP500 soft CL with swivel joint in the inlet
- Jet pipe CL with nozzle guard incl. high-pressure nozzle

MODEL VARIATIONS

Art.No.	Pressure bar	Flow Rate L/min	Motor Power kW	Nozzle	Power supply	Dimensions L mm x W mm x H mm	Weight kg approx.
H9318	350	18	11,0	040	400 V, 3 Phase, 50 Hz 460 V, 3 Phase, 60 Hz	860 x 600 x 1100	150
H9330	200	30	11,0	090			
H9335	170	35	11,0	110			
H9340	150	40	11,0	140			
H9415	500	15	15,0	030	400 V, 3 Phase, 50 Hz 460 V, 3 Phase, 60 Hz	860 x 600 x 1100	180
H9418	400	18	15,0	040			
H9421	350	21	15,0	050			
H9425	300	25	15,0	065			
H9430	250	30	15,0	080			
H9435	225	35	15,0	100			
H9440	200	40	15,0	130			
H9450	170	50	15,0	160			
H9521	500	21	18,5	040	400 V, 3 Phase, 50 Hz 460 V, 3 Phase, 60 Hz	860 x 600 x 1100	180
H9560	170	60	18,5	200			

SPECIAL EQUIPMENT AND CONFIGURATIONS

Through our modular system, we offer customized solutions tailored to your needs. We are happy to provide special configurations and equipment upon request. Contact us directly or visit our website for more information!