

The CLENA H5031 Series offers maximum robustness and durability and has been designed for the most demanding industrial environments and construction sites.

With a flushing performance of 30 L/min at 500 bar water pressure, these machines deliver outstanding results in applications such as concrete hydrodemolition, surface preparation, and tank cleaning.

**INCLUDED****Standard accessory kit from 400 bar:**

- 10 m high-pressure hose DN10, kink protection on both sides
- High-pressure gun HP500 soft CL with swivel joint in the inlet
- Jet pipe CL with nozzle guard incl. high-pressure nozzle

MODEL VARIATIONS

Art.No.	Pressure bar	Flow Rate L/min	Motor Power kW	Nozzle	Power Supply	Dimensions L mm x W mm x H mm	Weight kg approx.
H5031	500	30	30,0	055	400 V, 3 Phase, 50 Hz 460 V, 3 Phase, 60 Hz	1100 x 700 x 1130	400

SPECIAL EQUIPMENT AND CONFIGURATIONS

Through our modular system, we offer customized solutions tailored to your needs. We are happy to provide special configurations and equipment upon request. Contact us directly or visit our website for more information!

FINANCING OPTIONS

Benefit from flexible leasing and hire purchase options for our high-pressure systems – individually adapted to your requirements. We will be happy to provide you with a quotation. Simply send us an inquiry – we will advise you personally and without obligation.