



Mod. Awea VP-2012

with FANUC Oi-MF Plus CNC

with FANUC Oi-MF Plus CNC

Rif. nr. 1005

Year of manufacturing: 2023



The following data are indicative and we invite you to check them during your pleasant visit to our warehouse

CNC:		
Control		FANUC OI-MF Plus
Capacity:		
Distance between columns	mm	1300
Distance from spindle nose to table plane	mm	200-960
Spindle		
Max. spindle speed	r/min	10-6000
Spindle motor power (cont./ 30 min)	kW	15/18,5
Gear range change	nr°	2
Taper	ISO	50(DIN 69871)
Travel:		
Travel distance X/Y/Z axis	mm	2000x1200x760
Feedrate:		
Rapid traverse rate X/Y/Z	m/min	24/24/20
Table:		
Table size	mm	2000x1100
Automatic tool change:		
Tool storage capacity	nr.	40
Max. tool size (ØxL)	mm	125/229x350
Max. tool weight	Kg	15
Machine size		
Weight	Kg	16000
Dimension	mm	L 5700 W 3300 H 3700
Accessori presenti:		

Automatic high pressure system through the spindle at 20 bar, piece washing gun, BBT dual contact spindle. Total fairing with upper cover, chip conveyor with exit on the side opposite to that of the console 465 liter refrigerant collection tank, work area lighting lamp and 3-colour end-of-cycle alarm lamp