

Plate Rolling Machines KRM AT 10/3,0



SKU: 131970

All machines in this series feature asymmetrical rolls. This geometry provides optimum traction even with thin metal sheets in the stretch-bending phase for high-precision bending. The rear roll is fed manually. The upper roll swivels outward for easy removal of tube-shaped bent workpieces.

- Asymmetrical structure Main motor with brakes
- Hardened rollers with wire insertion
 - Conical bender

TECHNICAL SPECS

WORKING AREA

1050 mm
3 mm
1.5 mm
2 mm
90 mm
6 m/min
4/6/9 mm

DRIVE CAPACITY

Motor rating main drive 1.1 kW

MEASURES AND WEIGHTS

Overall dimensions (length x width x height)	1.63 m x 0.7 m x 1.2 m
Weight	480 kg











PRODUCT DETAILS

- 3-roller roll bender with asymmetrically positioned rollers
- Rigid machine frame made of ductile cast-iron Hardened rollers, suitable for stainless steel

- Main motor with brake system for exact bending
 Pull-out top roller with eccentric lock for easy workpiece removal
 Bottom and rear rollers include wire insertion grooves (standard equipment)

- Conical bending feature is included in standard equipment
 Manual feed or rear roller
 Mobile control panel with foot switch for left/right rotation

STANDARD EQUIPMENT

Conical bending feature Hardened rollers Wire insert groove Emergncy stop safety rope Seoarate control panel with foot switch Side cover Operator instructions

OPTIONAL EQUIPMENT

- digital readout for backroll, SKU: 253979
- motorized back roll adjustment backroll, SKU: 253980



KNUTH on YouTubeInformation to the point

On our YouTube channel you can find videos for nearly all machines from our program. We show the machines from current deliveries and you get an impression of the handling, the processing quality and the machining performance.

Are you interested in a machine for which you cannot find a current video? Please feel free to contact us!