

McIntyre 800HD Shear

DIMENSIONS & TECHNICAL SPECIFICATION



	ELECTRIC	DIESEL
BLADE LENGTH	813mm (32")	813mm (32")
TIP TO TIP OPENING	396mm (15.6")	396mm (15.6")
SHEARING HEIGHT	978mm (38.5")	978mm (38.5")
WEIGHT (WITH OIL)	1637 kg	TBC
OIL CAPACITY	316 Litres	316 Litres
NORMAL SOUND PRESSURE LEVEL	78 ± 3 dBA	TBC
PEAK SOUND PRESSURE LEVEL	84 ± 3 dBC	TBC
SOUND POWER LEVEL	82 ± 3 dBA	TBC
CUTTING CONTROL	SINGLE CUT - REPEATING	SINGLE CUT - REPEATING
STANDARD POWER SUPPLY	32A 3ph 380-415V 50Hz	12V BATTERY
MOTOR/ENGINE RATING	7.5kW (10hp) at 1450 rpm	7.5kW (10hp) at 1500 rpm
MAX SYSTEM PRESSURE	3500 psi (241 bar)	3500 psi (241 bar)
MAX SHEAR FORCE	120 TONNES	120 TONNES
CUTTING SPEED (MAX STROKE)	15 CYCLES/ MINUTE MAX	15 CYCLES/ MINUTE MAX
CUTTING SPEED (40% STROKE)	45 CYCLES/ MINUTE MAX	45 CYCLES/ MINUTE MAX

ISSUE B: MCINTYRE RESERVES THE RIGHT TO MAKE CHANGES OR IMPROVEMENTS TO OUR MACHINERY WITHOUT THE INCORPORATION OF SUCH CHANGES TO MACHINERY PREVIOUSLY SOLD.