
SCREEN DRUM COMPACT WITH DRUM EXTENSION **COMPOUND**



The Screen Drum ASCO® SD COMPACT with DEC (Drum Extension Compound) is assembled the DEC is used to screen coarse materials such as soil, gravel, wood chips, various types of waste and chip bundles and to provide an additional fraction. The system is ideal for the recycling industry.



△ TECHNICAL DATA

Drum length: 3,1 m.

Usable drum length: 2,5 m.

Outer diameter of the drum: 1,3 m Usable screening surface: 10,2 m²

System capacity: up to 35 m³/h.

Mesh size: 4 - 100 mm

⚠ Hopper opening: 2,24 m x 0,85 m. Speed (adjustable): 5 - 20 rpm

Drive power: 400V / 5,5 kW (optional 7,5 kW) Filling height: 1,81 m or 2,91 m (with support)

Weight: 1955 kg Length: 4,33 m /\ Width: 2,36 m

Height: 1,81 m or 2,91 m (with support) Recommended amperage for fuses: 16 A

igstyle igstyle igstyle DRUM OPTIONS



SEGMENT DRUM WITH MESHES - for grit/ gravel/crushed stone, soil, building rubble without bricks, wood chips.

The screen meshes are replaceable. Max. weight per piece of material is 5 kg.



ROUND DRUM - for stones, grit/gravel/ crushed stone, earth, building rubble, wood chips.

Max. Weight per piece of material is 10 kg.



HEXAGONAL DRUM WITH REPLACEABLE PLATES - for stones, grit/gravel/crushed stone, earth, building rubble, wood chips, metal chips.

Max. weight per piece of material is 10 kg.



Vibration motors for emptying the hopper

Drum rotation in both directions

Better screening quality Different drum variants

Three fractions of the material.

Cleaning brushes

Easy drum replacement

Hourcounter



SEGMENT DRUM WITH PERFORATED SCREEN SHEETS - for grit/gravel/crushed stone, soil, building rubble without bricks, wood chips. The screen meshes are interchangeable.

Max. weight per piece of material is 5 kg.



ROUND DRUM WITHOUT SPIRALS - for stones, grit/gravel/crushed stone, earth, building rubble, wood chips.

Max. Weight per piece of material is 10 kg.



DOUBLE PERFORATED DRUM - for stones, grit/gravel/crushed stone, soil, building rubble, wood chips.

Max. Weight per piece of material is 10 kg.

△ ADDITIONAL OPTIONS



Bunker

Impresses with its throughput performance. Designed as an addition to the SD Compact for continuous material input or as a stand-alone solution for a long service life.






Segment support

plate with two



Bar sizer



Washer

The washer enables material to be washed screen drum operation.




Support plate

Compact design and easy installation, ensure high stability.

Concrete holder



Grid



Remote control

Speed and rotation direction of the screen drum can be adjusted by the remote control



Mobile support plate

Mobile support with three height adjustment options: 1,1 m, 1,35 m and 1.6 m.



Barrier

Prevents mixing of differently graded materials and separates them into two fractions. The width of the barrier is 1.3 m.



Top cover

The top cover for the SD Compact reduces dust and noise pollution.





and moistened during the

