

Produktdetail:

Code: P00457

Vorlage: PLASMA 1050 LCD INVERTER

The three-phase power source with inverter technology for metal plasma cutting, PLASMA 1050 LCD INVERTER is characterized by compact design, low weight, user-friendliness and cutting high-efficiency with optimal surface quality.

It's suitable for heavy metal work and for heavy-duty work cycles, for manual and automatic production applications in industrial and craft sectors.

The optional CNC interface, the display and the synergy allows an easy integration with pantographs.

The recommended cutting thickness on steel is from 32 mm to 38 mm. The separation thickness is 50 mm.

The lack of High-Frequency start makes it possible to work next to computers, medical equipment, instruments and any other electronic device sensitive to high frequency emissions.

It can be connected to motor-driven generators of adequate power.

MAIN FEATURES

- Automatic setting of appropriate voltage within the following ranges: 3x208/220/230V and 400/440V.
- Pilot Arc to cut painted or coated metals.
- Suitable for plasma gouging.
- Self Restart Pilot function for nets and grids cutting.
- Ultra Cut Capacity technology to improve the cutting capacities on high thicknesses.
- Innovative Thin Cut technology that allows to obtain cuts of superior quality and reduced kerf (amount of removed material).
- Hyper Speed Cut technology enhancing the cutting speed.
- Multi Piercing technology: possibility of piercing on high thickness in a shorter time and with less wear of consumables.
- Extra Life technology that increases performances and duration of consumables.
- The graphic LCD display with operator synergic interface especially useful for mechanized cuttings.
- Microprocessor-controlled cutting parameters and functions.
- Possibility to activate a security password.
- Safety systems on the torch.
- Its standard equipment includes a 6 meter-long hand torch and a grounding cable.

OPTIONAL FUNCTIONS

- CNC interface to exchange the main cutting signal with the automatic CNC bench.



Datenblatt:


Code	P00457		
Item	PLASMA 1050 LCD INVERTER		
Input Voltage	3x208-220-230V 50-60HZ	3x400-440V 50-60HZ	
Absorbed power	50% 13,9 kVA 60% 11,3 kVA 100% 10,1 kVA	60% 16,6 kVA 100% 14,3 kVA	
Cutting current	20÷85 A	20÷105 A	
Duty cycle – 10 MIN CYCLE ACCORDING TO EN 60974-1	50% 85A - 60% 75A - 100% 65A	60% 105A - 100% 90A	
Air pressure	5,7-5,8 bar		
Air flow	250 l/min		
Cut thickness on steel	32 - 38 mm		
Max separation cut	50 mm		
Piercing	20 mm		
Protection class	IP 23		
Construction standards	EN60974 – 1 / EN60974 – 7 / EN60974 – 10		
Dimensions	220x540x460h mm		
Weight	25 kg		

Zubehör:

 535438 6m, hand torch ECF-131


 535437 (optional) 12m, hand torch ECF-131


 535436 (optional) 6m, machine torch ECF-131



535435 (optional) 12 m, machine torch ECF-131



535465 (optional) ECF-131 hand torch with 15° inclination, 1.30 m grip and EASY FIT connection



535472 (optional) ECF-131 hand torch with 15° inclination, 0.80 m grip and EASY FIT connection




356588 (optional) 15 m torch cable with EASY FIT for torches code 535465 and 535472



356587 (optional) 7,5 m torch cable with EASY FIT for torches code 535465 and 535472



540154.B (optional) MINI KIT for handtorch ECF-131 (105A)



540090.B (optional) Consumables kit for first use.



309462 (optional) Wheeled compasses for P25 ST-130 / ECF-131



356450 (optional) Wheeled torch holder for P25 ST-130 ECF-131



580006 (optional) Fahrwagen für Transport



309489 (optional) Non-stick spray



357227 (optional) Compressed air filter with filtering cartridge to protect torches against impurities present in compressed air (oil and/or water).



370001 (optional) Cartridges for air filter, package of 8 pieces.



309073 (optional) Helm mit LCD-Filter (9-13 DIN).



540051 (optional) Computer-pantograph kit
