



# **KOLLTRONIC**<sup>®</sup> Workstation

Products of the **KOLLTRONIC**® series are used for cost optimised, premium laser marking and are ideal to be integrated in industrial production lines or work as a stand alone machine.

- · Beneficial dimension and robust housing
- Available with rotary axis, and CNC axis
- Flexible also available as XXL-Version

High coding accuracy, crisp and sharp codes with fiber laser on metals, plastics, and with Co2 Laser on paper, wood, glass, acrylics etc. Very fine spot for utmost precision, ideal for static and mark-on-the-fly applications. Compact sizing and flexible integration options Very long expected laser life. Lasting performance without planned maintenance routines ensuring high uptime.







### **APPLICATION**

SK LASER offers several power options and can code human readable texts, graphics, variable and serialised data as well as 2D codes onto a variety of substrates including metall, plastics, cartons, glass, paper.

A wide range of industries benefit of this laser technology, such as Automotive, Electronics, Metall, Plastics, Medical, Electrical, Aerospace etc.

## Workstation

Easy to Use

### WORKSTATION

### **System**

Working area Working table

Max. item size

**Dimensions** 

Weight Power suply Cooling Mechanical lifting Fume extraction

**Options** 

120 x 120 mm, 180 x 180 mm, 210mm x 210mm

Standard =400 x 600 mm,

 $XL = 400 \times 800 \text{ mm}$ 

Standard =W x H x L 620 x 320 x 400 mm

 $XL = W \times H \times L 820 \times 320 \times 400 \text{ mm}$ 

800 x 1800 x 940 mm (F10, F20, F30, F50, F75, G3)

800 x 1800 x 1600 mm (C10, C30, C60, C100, C200)

 $(W \times H \times L)$ 180 kg

230V/5A, 50 Hz

Air 500 mm

Fume extraction optional available

adapter with 50 mm diameter

Different F-Theta lens sizes

Rotary axis **CNC** axis Rotary table

Others subject to testing

### Foil Marking Machine







**Tunnel Version** 









Überzeugende Lösungen – Innovative Technologie

#### **SK Laser GmbH**

Daimlerring6 65205 Wiesbaden Germany Tel. +49 (0) 6122 53335-0 Fax +49 (0) 6122 53335-29

